

GLYPTAL INC -- GLYPTAL -- 5970-00-900-9372

=====
Product Identification
=====

Product ID:GLYPTAL

MSDS Date:07/14/1994

FSC:5970

NIIN:00-900-9372

MSDS Number: BKYNX

=== Responsible Party ===

Company Name:GLYPTAL INC

Address:305 EASTERN AVE

City:CHELSEA

State:MA

ZIP:02150-3344

Country:US

Info Phone Num:617-884-6918

Emergency Phone Num:617-884-6918

CAGE:65313

=== Contractor Identification ===

Company

Name:GLYPTAL INC

Address:305 EASTERN AVE

Box:NONE

City:CHELSEA

State:MA

ZIP:02150-3344

Country:US

Phone:617-884-6918

CAGE:65313

Company Name:THE SMITH GROUP INC.

Address:811 E. CAYUGA STREET

Box:City:PHILADELPHIA

State:PA

ZIP:19124-3893

Country:US

Phone:215-743-8200

CAGE:2B613

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 34.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100

PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VARNISH MAKERS & PAINTER NAPHTHA
CAS:8030-30-6
Fraction by Wt: 5.6%
Other REC Limits:NONE RECOMMENDED

Ingred Name:STODDARD SOLVENT,
CAS:64741-41-9
Fraction by Wt: 0.2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE
CAS:1309-38-2
RTECS #:OM4800000
Fraction by Wt: 8.2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 16.9%
Other REC Limi
ts:NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:0.2 FIBERS/CC; 9192

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: IRRITATION, DEFATTING, DRYING, &
DERMATITIS. EYES: IRRITATION. INHALATION: CENTRAL NERVOUS SYSTEM
DEPRESSION, HEADACHES, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS.
INGESTION: VOMITING, CHEMICAL
PNEUMONITIS, & PULMONARY
EDEMA/HEMORRHAGE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SKIN: IRRITATION, DEFATTING, DRYING, &
DERMATITIS. EYES: IRRITATION. INHALATION: CENTRAL NERVOUS SYSTEM
DEPRESSION, HEADACHES, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS.
INGESTION: VOMITING, CHEMICAL PNEUMONITIS, & PULMONARY
EDEMA/HEMORRHAGE.
Medical Cond Aggravated by Exposure:PRE-EXISTING LIVER AND/OR KIDNEY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE.

=====

===== First Aid Measures =====

First Aid:INGESTION: IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS, CAN CAUSE CHEMICAL PNEUMONITIS & PULMONARY EDEMA/HEMORRHAGE. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN OR CPR IF NEEDED. EYES:FLUSH W/PLENTY OF WATER. SKIN: WASH THOROUGHLY W/WATER. USE HAND LOTION. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:72F
Lower Limits:1%
Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS W/POSITIVE PRESSURE MODE. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL TO REDUCE PRESSURE.
Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO HEAT MAY CAUSE PRESSURE BUILD-UP. FLAMMABLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:USE AN ABSORBENT MATERIAL SUCH AS VERMICULITE TO REMOVE SPILLED MATERIAL. PROVIDE ADEQUATE VENTILATION.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, WELL-VENTILATED AREA. AVOID EXCESSIVE HEAT, SPARKS, & OPEN FLAMES. GROUND CONTAINERS & TRANSFER VESSELS.
Other Precautions:KEEP FREE FALL OF LIQUID TO A FEW INCHES TO AVOID BUILD-UP OF STATIC ELECTRICITY. DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREAS USE AN APPROVED SELF-CONTAINED RESPIRATOR.
Ventilation:KEEP AIR
Spec Gravity:9.91 LB/GL
Evaporation Rate & Reference: