View NSN Online: https://aerobasegroup.com/nsn/5970-00-090-9184

COLUMBIA CHASE CORP. HUMISEAL DIV. -- HUMISEAL 1B31 -- 5970-00-090-9184

Product ID:HUMISEAL 1B31 MSDS Date:06/12/1991

FSC:5970

NIIN:00-090-9184

MSDS Number: BKZWK === Responsible Party ===

Company Name: COLUMBIA CHASE CORP. HUMISEAL DIV. Address: 26-60 BROOKLYN QUEENS EXPRESSWAY WEST

Box:445

City:WOODSIDE

State:NY

ZIP:11377-0445 Country:US

Info Phone Num:718-932-0

800

Emergency Phone Num:718-932-0800

CAGE:EO647

=== Contractor Identification ===

Company Name: ARGENT INDUSTRIES INC

Address:477 E WENGER ROAD

Box:City:ENGLEWOOD

State:OH ZIP:45322 Country:US

Phone:937-836-8633

CAGE:25579

Company Name: COLUMBIA CHASE CORPORATION

Box:445

CAGE:EO647

Company Name: HUMISEAL DIVISION/CHASE CORPORATION Address: 26-60 BROOKLYN QUEENS EXPRESSWAY WEST

Box:City:WOODSIDE

State:NY ZIP:11377 Country:US

Phone:718-932-0800

CAGE:99109

====== Composition/Information on Ing

redients =======

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 47-53%

Other REC Limits: NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 13-18%

Other REC Limits: NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ACRYL

IC POLYMER

Fraction by Wt: 32-38%

Other REC Limits: NONE SPECIFIED

=========== Hazards Identification ==========================

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 5G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYE CONTACT MAY RESULT IN SLIGHT IRRITATION & CONJUNCTIVITIS. INHALATION CAUSES CENTRAL NERVOUS SYSTEM DEPRESSION. MAY CAUSE RESPIRATOR DEPRESSION, CONVULSION

S, CARDIAC ARRHYTHMIAS AND DEATH. I NGESTION CAUSES
BURNING SENSATION IN MOUTH & STOMACH. CHRONIC:CORNEAL BURNS, SKIN
IRRITATION & DERMATITIS.

Explanation of Carcinogenicity: NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure: VAPOR IS IRRITATING TO EYES & MAY CAUSE DIZZINESS, WEAKNESS, HEADACHE, NAUSEA, ETC. ASPIRATION OF VOMITUS INTO LUNGS AFTER INGESTION MAY RESULT IN CHEMICAL PNEUMONITIS AND PULMONARY EDEMA/HEM

ORRHAGE A ND MAY BE FATAL. ABSORPTION THROUGH
SKIN MAY ADD SIGNIFICANTLY TO EXPOSURE. LIQUID CAN CAUSE DEFATTING
& DRYING OF SKIN.

Medical Cond Aggravated by Exposure: ANY RESPIRATORY DISORDER OR SKIN CONDITION SUCH AS DERMITITIS.

First Aid:INHALATION: REMOVE TO FRESH AIR & PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION. EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET

MEDICAL ATTENTION. SKIN:

REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS. GET MEDICAL ATTENTION.

========== Fire Fighting Measures ===============

Flash Point Method:TCC Flash Point:30.0F,-1.1C

Lower Limits: 1.6 Upper Limits: 11.2

Extinguishing Media: USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE F

IGHTING PROTECTIVE EQUIPMENT AND A

FULL FACED SELF CONTAINED BREATHING APPARATUS. FIGHT AS A FLAMMABLE LIQUID FIRE.

Unusual Fire/Explosion Hazard: VAPOR IS FLAMMABLE AND HEAVIER THAN AIR AND MAY TRAVEL TO SOURCE OF IGNITION AND FLASHBACK.

======== Accidental Release Measures ============

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. PROVIDE VENTILATION AND/OR RESPIRATORY PROTECTION. CONTAIN AND REMOVE WITH INERT ABSORBENT (SAND,


VERMICULITE, ETC.) AND NON-SPARKING TOOLS.

Neutralizing Agent:NONE

=========== Handling and Storage ==============

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS & OPEN FLAMES. STORE AT AMBIENT TEMPERATURE. GROUND TO PROTECT FROM STATIC CHARGE. KEEP CONTAINER CLOSED. USE VENTILATION.

Other Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. VAPORS MAY CAUSE FLASH FIRE. AVOID CONTACT WITH EYES AND CLOTHING. AVOID PROLONGED OR REP



Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE.

======= Disposal Considerations ============

Waste Disposal Methods:DISPO

SAL OF HUMISEAL PRODUCTS REQUIRES STRICT
COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS PERTAINING TO
DISPOSING HAZARDOUS WASTE MATERIALS. CONTACT THE APPROPRIATE
ENVIRONMENTAL AGENCIES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all I iability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.