

DEL PAINT MFG. -- TT-P-29J TYPE I -- 8010-00-598-5733

===== Product Identification =====

Product ID:TT-P-29J TYPE I

MSDS Date:09/04/1990

FSC:8010

NIIN:00-598-5733

MSDS Number: BKZZQ

=== Responsible Party ===

Company Name:DEL PAINT MFG.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:ONEY FLE

MING

CAGE:DELPA

=== Contractor Identification ===

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

Company Name:DEL PAINT MFG.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

Country:US

Phone:405-672-1431

CAGE:DELPA

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 3.03%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PP

M,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISBUTYRATE (TEXANOL
ESTER ALCOHOL

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 0.65%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NONE

ACGIH TLV:NONE

Ingred Name:VOC: 1.22 LBS/GL

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:MAY

CAUSE SOME NAUSEA IF INGESTED.

Effects of Overexposure:CAN CAUSE IRRITATION OF RESPIRATORY PASSAGES.

=====
===== First Aid Measures =====

First Aid:IF INGESTED: GIVE 2 GLASSES OF WATER AND INDUCE VOMITING.

SKIN: FLUSH WITH WATER. EYES: FLUSH WITH WATER. INHALATION: NO

EMERGENCY CARE ANTICIPATED.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:NA

Autoignition Temp:Autoignition Temp Text:241F

Lower

Limits:.06

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:THIS PRODUCT WILL NOT BURN UNTIL THE

WATER HAS EVAPORATED. FOR RESIDUAL SOLID, USE METHODS DESCRIBED
ABOVE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL.

MINOR SPILLS MAY BE FLUSHED TO SEWER IF LOCAL REGULATIONS PERMIT.

=====
===== Handlin

g and Storage =====

Handling and Storage Precautions:PROTECT FROM FREEZING.

Other Precautions:DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER-SPRAY DURING SPRAY APPLICATION.

Ventilation:NORMAL, SUCH AS A FAN.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Supple

mental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212 TO 387F

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:212F,100C

Vapor Pres:NONE

Vapor Density:> AIR

Spec Gravity:1.55

pH:8.5-*

Viscosity:82-110 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:WHITE LIQUID WITH FAINT ODOR.

Percent Volatiles by Volume:67.22

Corrosion Rate:*9.5

===== Stabil

ity and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:DO NOT TAKE INTERNALLY.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:BURY IN A LANDFILL WHERE PERMITTED UNDER APPROPRIATE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of t

he Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.