

UNITED STATES GYPSUM COMPANY -- SHEETROCK ACOUSTICAL SEALANT -- 8030-00-422-7359

===== Product Identification =====

Product ID:SHEETROCK ACOUSTICAL SEALANT

MSDS Date:10/02/1989

FSC:8030

NIIN:00-422-7359

MSDS Number: BLCZN

=== Responsible Party ===

Company Name:UNITED STATES GYPSUM COMPANY

Address:101 S WACKER DR

City:CHICAGO

State:IL

ZIP:60606-4385

Country:US

Emergency Phone Num:312-606-4542

CAGE

:61357

=== Contractor Identification ===

Company Name:UNITED STATES GYPSUM CO

Address:101 S WACKER DR

Box:City:CHICAGO

State:IL

ZIP:60606-4302

Country:US

Phone:312-606-4000 (EMERG /4542)

CAGE:61357

===== Composition/Information on Ingredients =====

Ingred Name:CARBONIC ACID, CALCIUM SALT (1:1); (CALCIUM CARBONATE)

CAS:471-34-1

RTECS #:FF9335000

Fraction by Wt: 50-60%

OSHA PEL:5 MG/M3 (R DUST)

ACGIH TLV:10 MG/M3 (T DUST)

Ingred Name:VINYL ACRYLIC COPOLYMER (MIXTURE OF ING 2 A

ND ING 13 IS 5 -

35%)

CAS:25586-24-7

Fraction by Wt: 5-35%

Ingred Name:BUTYL BENZYL PHTHALATE (SARA III)

CAS:85-68-7

RTECS #:TH9990000

Fraction by Wt: 5-10%

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 1-3%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:GLYCOLS, POLYETHYLENE, MONO (NONPHENYL) ETHER; (NONYLPHENOL
POLYETHOXATE)

CAS:9016-45-9

RTECS #:MD090000

0

Fraction by Wt: 0-1%

Ingred Name:ZINC, BIS (DIMETHYLDITHIOCARBAMATO);(ZIRAM)

CAS:137-30-4

RTECS #:ZH0525000

Fraction by Wt: .05-.20%

Ingred Name:ETHYL ACRYLATE METHACRYLIC ACID COPOLYMER

CAS:28411-49-6

Fraction by Wt: 0-0.5%

Ingred Name:SODIUM PHOSPHATE, TRIBASIC (SARA III)

CAS:10124-56-8

RTECS #:OY3675000

Fraction by Wt: 0-0.4%

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM SALT OF POLYMERIC ACARBOXYLIC ACID

Fraction by Wt: 0-0.2%

Ingred Name:BICYCLICOXAZOLIDINES

CAS:56709-1

3-8

Fraction by Wt: 0-0.2%

Ingred Name:AMMONIUM HYDROXIDE (SARA III)

CAS:1336-21-6

RTECS #:BQ9625000

Fraction by Wt: 0-0.1%

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: TRACE

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:VINYL ACRYLIC COPOLYMER (MIXTURE OF ING2 AND ING13 IS 5-35%

CAS:25767-47-9

Fraction by Wt: 5-35%

Other REC Limits:NONE SPECIFIED

OSHA PEL:N/K

ACGIH TLV:N/K

=====
Hazards Ident
ification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES/SKIN: MAY CAUSE CHEMICAL/
MECHANICAL IRRITATION. INHAL: HARMFUL IF FUMES ARE INHALED. MAY
CAUSE IRRITATION OF UPPER RESPIRATORY TRACT. INGEST: UNLIKELY TO
OCCUR BUT HARMFUL OR FATAL IF SWALLOWED. CAUSES VOMITING, DIARRHEA
& DEPRESSED RESPIRATION

. CHRONIC: EYES: NONE KNOWN. SKIN: NONE
KNOWN. (EFFECTS OF OVEREXPOSURE)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HEALTH HAZARD: INHAL: REPORTS HAVE ASSOCIATED
PROLONGED & REPEATED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN
& NERVOUS SYSTEM DAMAGE. INGEST: WHILE UNLIKELY TO OCCUR, INGESTION
OF ETHYLENE GLYCOL IN EXCESS MAY LEAD TO RESPIRATORY & CARDIAC
FAILURE, & KIDNEY & LIVER DAMAGE. TARGET ORGANS: LUNGS/LIVER/KIDNEY
& HEART.

Medical Conditions Aggravated by

Exposure:PRE-EXISTING UPPER RESPIRATORY AND LUNG DISEASES SUCH AS, BUT NOT LIMITED TO, BRONCHITIS, EMPHYSEMA AND ASTHMA.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH THOROUGHLY WITH WATER FOR AT LEAST 15 MIN TO REMOVE PARTICLES. IF IRRITATION CONTINUES, SEE PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. INHAL: REMOVE TO FRESH AIR. INGEST: CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:WATER, FOAM, CARBON DIOXIDE AND DRY CHEMICAL.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
Accidental Release Measures
=====

Spill Release Procedures:SCOOP UP. WASH DOWN AREA BEFORE MATERIAL DRIES.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .
Ventilation:GENERAL MECHANICAL.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SP

ECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212F,100C
Spec Gravity:1.5
Solubility in Water:EMULSION
Appearance and Odor:MEDIUM PASTE, BLACK; SWEET ACRYLIC ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE SPECIFIED BY MANU
FACTURER.
Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:TO SANITARY LANDFILL IN ACCORDANCE WITH LOCAL,
FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this in
formation to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.