

DAVIS-HOWLAND OIL CORPORATION -- INLAND 43 -- 9150-00-273-8663

===== Product Identification =====

Product ID:INLAND 43

MSDS Date:09/07/1990

FSC:9150

NIIN:00-273-8663

MSDS Number: BLFFH

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-473-6651

Emergency Phone Num:716-473-6651

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY
PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500

Fr

action by Wt: 100%
Other REC Limits:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ON RARE OCCASIONS, PROLONGED AND REPEATED EXPOSURE TO OIL MIST POSES A RISK OF PULMONARY DISEASE SUCH AS CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS. ASPIRATION MAY LEAD TO CHEMICAL PNEUMONITIS.
Explanation of Carcinogenicity:THIS PRODUCT IS NOT LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN, MUTAGEN, TERATOGEN OR NEUROTOXIN.
Effects of Overexposure:GENERALLY CONSIDERED MINIMALLY IRRITATING TO THE EYES AND MILDLY IRRITATING TO THE SKIN. PROLONGED AND REPEATED CONTACT IS NOT EXPECTED TO CAUSE SKIN DISORDERS SUCH AS DERMATITIS OR SENSITIZATION. INHALATION OF VAPOR OR OIL MIST MAY CAUSE MILD UPPER RESPIRATORY TRACT IRRITATION. INGESTION MAY CAUSE NAUSEA.
Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP & WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS. INHALATION: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF REQUIRED. EYE: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GIVE LIQUIDS & INDUCE VOMITING IF VICTIM IS CONSCIOUS. WASH OUT SMALL AMOUNTS IN MOUTH. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:446F,230C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, OR FOAM
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACE

CEDED SELF CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES
IN ENCLOSED SPACES.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILLS MAY BE WIPED UP WITH A RAG. LARGE SPILLS SHOULD BE PICKED UP IMMEDIATELY WITH AN ABSORBENT. IF PRODUCT ENTERS ANY WATER COURSES, SEWERS OR EXTENSIVE LAND AREAS, CONFORM WITH APPLICABLE GOVERNMENT REGULATIONS.

===== Handling and Storage =====

Handling and Storage Precautions:NONE

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES OR AN ATMOSPHERE-SUPPLYING RESPIRATOR IF REQUIRED. PROTECTION IS NOT REQUIRED UNDER NORMAL USE CONDITIONS.

Ventilation:MECHANICAL EXHAUST AND/OR LOCAL VENTILATION RECOMMENDED IF MIST EXCEEDS THE RECOMMENDED TWA OF 5 MG/M3.

Protective

Gloves:OIL RESISTANT GLOVES (NITRILE BEST)

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS.

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices:MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

THIS PRODUCT IS CLASSIFIED AS AN OIL UNDER SECTION 311 OF THE CLEAN WATER ACT. SPILLS ENTERING SURFACE WATERS OR ANY WATER COURSES OR SEWERS ENTERING/LEADING TO SURFACE WATER

S THAT CAUSE A SHEEN MUST

BE REPORTED TO THE NATIONAL RESPONSE CENTER. 800-424-8602

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>392F,>200C

Vapor Pres:200

C.

Hazardous Decomposition Products:CARBON MONOXIDE AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED UPON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:PROPER WASTE DISPOSAL PROCEDURES ARE DEPENDENT ON THE PR

PRODUCT'S END-USE. CHECK APPLICABLE FEDERAL, STATE AND LOCAL
COVERING TREATMENT, STORAGE AND DISPOSAL OF YOUR PROCESS EFFLUENTS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek com
petent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.