

TACC INTERNATIONAL CORP. -- NEOPRENE SOLVENTBORNE ADHESIVE, MA-212 --
8040-00-290-4301

=====
===== Product Identification =====

Product ID:NEOPRENE SOLVENTBORNE ADHESIVE, MA-212

MSDS Date:07/01/1989

FSC:8040

NIIN:00-290-4301

MSDS Number: BLJHN

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phon

e Num:617-878-7015

Emergency Phone Num:617-878-7015

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
===== Composition/Information on Ingredients =====

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 37-58%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt

Qty:1 LB

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 16-25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 9-15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS

:108-88-3

RTECS #:XS5250000

Fraction by Wt: 2-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:ACUTE: HEADACHE, DIZZINESS, NAUSEA,
UPPER RESPIRATORY DRYNESS, IRRITATION, DROWSINESS, MENTAL
DEPRESSION, NARCOSIS, DIFFICULTY IN BREATHING. CHRONIC: COULD LEAD

TO PERMANENT EFFECTS TO THE NERVOUS SYS TEM, BODY ORGANS OR THE
BRAIN. USE WITHADEQUATE VENTILATION.

Effects of Overexposure:EYES: IRRITATION. SKIN: REMOVAL OF SKIN OILS,
IRRITATION, DERMATITIS, EVEN SENSITIZATION WITH OVEREXPOSURE.
INGESTION: MAY BE HARMFUL OR FATAL IF SWALLOWED.

=====
===== First Aid Measures =====

First Aid:INHALATION: GET FRESH AIR. EYES: FLUSH WITH WATER FOR AT
LEAST 15 MINUTES. IF NECESSARY, CALL A PHYSICIAN. SKIN: WAS

H WITH

SOAP AND WATER. INGESTION: CALL POISON CENTER IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:CC

Flash Point:1 (BUTYL ACETATE = 1)

Solubility in Water:NIL

Appearance and Odor:NEUTRAL, TYPICAL ODOR.

Percent Volatiles by Volume:63

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES.

Stability Condition to Avoid:FIRE, SPARKS,

STATIC ELECTRICITY.

Hazardous Decomposition Products:CO AND CO2.

=====
Disposal Considerations
=====

Waste Disposal Methods:LIQUID MATERIAL IS DESIGNATED AS HAZARDOUS WASTE UNTIL ALL SOLVENTS AND VAPORS HAVE EVAPORATED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use

by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.