

GENERAL ELECTRIC CO., SILICONE PRODUCT DIV. -- SEA200A -- 8030-00-585-5361

=====  
Product Identification  
=====

Product ID:SEA200A

MSDS Date:03/22/1988

FSC:8030

NIIN:00-585-5361

Kit Part:Y

MSDS Number: BLJJN

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO., SILICONE PRODUCT DIV.

Address:HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergency P

hone Num:518-237-3330

Preparer's Name:DA POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NONHAZARDOUS INGREDIENTS

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes

of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INGESTION: MAY CAUSE STOMACH  
DISCOMFORT. SKIN CONTACT: MAY CAUSE MILD SKIN IRRITATION. EYE  
CONTACT: MAY CAUSE MILD EYE IRRITATION.

=====  
First Aid Measures  
=====

First Aid:INGESTION: RINSE MOUTH WITH WATER SEVERAL TIMES. SKIN: WASH  
WITH SOAP AND WATER. EYES: IN CASE OF CONTACT, IMMEDIATELY FLUSH  
EYES WITH PLEN  
TY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL  
ATTENTION IF IRRITATION PERSISTS.

=====  
Fire Fighting Measures  
=====

Flash Point Method:PMCC  
Flash Point:>250F,>121C  
Extinguishing Media:USE WATER FOR, CARBON DIOXIDE, FOAM OR DRY  
CHEMICAL.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explos  
ion Hazard:COMBUSTION MAY CAUSE PRODUCTION OF  
HAZARDOUS DECOMPOSITION PRODUCTS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL  
AND PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES WITH  
DETERGENT AND WATER TO REDUCE SLIPPING HAZARD.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID CONTACT WITH SKIN AND EYES.

=====  
Exp  
posure Controls/Personal Protection  
=====

Ventilation:LOCALIZED VENTILATION SHOULD BE USED TO CONTROL DUST  
LEVELS.  
Protective Gloves:CLOTH GLOVES.  
Eye Protection:SAFETY GLASSES.  
Other Protective Equipment:EYEWASH STATIONS.  
Supplemental Safety and Health  
KEY1=N1.

=====  
Physical/Chemical Properties  
=====

HCC:F4  
Vapor Density:NEG.  
Spec Gravity:1.44  
Evaporation Rate & Reference:NEG. (BUTYL ACETATE=1)  
Solubility in Water:NEG.  
Appearance and Odor:BEIGE LI

QUID; ODORLESS

Percent Volatiles by Volume: