

N/P -- 601900, ZPG-1015 -- 8030-00-709-3327

Product ID:601900, ZPG-1015

MSDS Date:01/01/1987

FSC:8030

NIIN:00-709-3327

MSDS Number: BLJJY

=== Responsible Party ===

CAGE:4W458

=== Contractor Identification ===

Company Name:ZIEBART INTERNATIONAL CORP ZIEBART PRODUCTS GROUP

Address:26500 CAPITOL AVE

Box:City:REDFORD

State:MI

ZIP:48239-2506

Country:US

CAGE:4W458

=====
===== Composition/Information on Ingredients =====

In
gred Name:PETROLEUM DISTILLATES

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:AS OIL MIST 5MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 31%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:VOC: 3.2 LB/GAL (NO H2O) GRAMS/LITER

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of E

Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards Acute and Chronic: ACUTE: SYMPTOMS RANGE FROM MILD DEPRESSION TO CONVULSIONS AND LOSS OF CONSCIOUSNESS. SKIN CONTACT CAUSES IRRITATION. CHRONIC: SKIN DEFATTING AND DERMATITIS. INHALATION SYMPTOMS AS ABOVE.

Explanation of Carcinogenicity: NO CANCER CAUSING AGENT.

Effects of Overexposure: SKIN: IRRITATION/RASH. INGESTION: VOMITING, DIARRHEA AND GASTROINTESTINAL PAIN. INHALATION: NAUSEA, SHORTNESS OF BREATH, DIZZINESS.

Medical Conditions Aggravated by Exposure: SKIN, LIVER, KIDNEY AND C.N.S. DISORDERS.

=====
===== First Aid Measures =====

First Aid: INHALATION: REMOVE TO FRESH AIR, GIVE OXYGEN, CONTACT PHYSICIAN. EYES: FLUSH WITH WATER. CONTACT PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING, WASH WITH WATER. INGESTION: DO NOT INDUCE VOMITING, CONTACT PHYSICIAN; GIVE WHITE MINERAL OIL.

=====
===== Fire Fighting Measures =====

Flash Point: 101 F
, 38 C; PMCC
Autoignition Temp: Autoignition Temp Text: 427 C

=====
===== Accidental Release Measures =====

Spill Release Procedures: REMOVE SOURCES OF IGNITION, PROVIDE ADEQUATE VENTILATION, ABSORB WITH VERMICULITE OR OTHER ABSORBENT. SPILLED MATERIAL IS A HAZARDOUS WASTE.

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION.
Other Precautions: PREVENT SKIN CONTACT AND AVOID BREATHING VAPORS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE AT > TLV. USE SELF-CONTAINED BREATHING APPARATUS AT >10 TIMES THE TLV.
Ventilation: LOCAL EXHAUST. MAINTAIN ADEQUATE TRANSFER VELOCITY TO PREVENT EXPLOSIVE CONCENTRATIONS. ELIMINATE SOURCE OF IGNITION.
Protective Gloves: BUNA-N-RUBBER GLOVES
Eye Protection: GOGGLES OR FACE SHIELDS
Other Protective

Equipment:USE BUNA-N-RUBBER APRON
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Viscosity:1500-4000*

===== Stability and Reactivity Data =====

Hazardous Decomposition Products:OXIDES OF CARBON, NITROGEN AND SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS EPA HAZARDOUS WASTE NUMBER D001 BY
INCINERATION OR STABILIZATION AT AN EPA LICENS
ED FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
part
icular situation.