

ARMSTRONG WORLD INDUSTRIES INC -- 520 ADHESIVE -- 8040-00-841-9773

=====
Product Identification
=====

Product ID:520 ADHESIVE

MSDS Date:03/07/1986

FSC:8040

NIIN:00-841-9773

MSDS Number: BLJKM

=== Responsible Party ===

Company Name:ARMSTRONG WORLD INDUSTRIES INC

Address:LIBERTY AND CHARLOTTE STREETS

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Info Phone Num:717-396-2729 OR 396-2935

Emerg

ency Phone Num:717-396-2729 OR 396-2935

Preparer's Name:D. E. BOUDER

CAGE:03938

=== Contractor Identification ===

Company Name:ARMSTRONG WORLD INDUSTRIES, INC.

Address:313 W. LIBERTY ST.

Box:3209

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328; 717-396-2935

CAGE:03938

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000PPM

ACGIH TLV:75

0PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA (LIGROINE)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 35%
Other REC Limits:NONE SPECIFIED
OSHA PEL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

Ingred Name:SYNTHETIC RUBBER
Fraction by Wt: 13%
Other REC L
imits:NONE SPECIFIED

Ingred Name:PHENOLIC RESIN
CAS:28470-78-2
Fraction by Wt: 9%
Other REC Limits:NONE SPECIFIED

Ingred Name:RUBBER CURING INGREDIENTS
Fraction by Wt: 3%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF RESPIRATORY
TRACT, COUGHING, HEADACHE, DIZZINESS, DROWSINESS, NAUSEA,
UNCOORDINATED MOVEMENTS. SKIN A

ND EYES: EXCESSIVE SKIN CONTACT MAY
CAUSE DRYING AND CRACKING OF THE SKIN AND RESULT IN DERMATITIS.
CONTACT WITH EYES WILL CAUSE IRRITATION AND DEFATTING OF TISSUE.

=====
First Aid Measures
=====

First Aid: INHALATION; REMOVE TO FRESH AIR IF EXPOSED TO EXCESS
CONCENTRATION OF VAPOR. SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.
SKIN AND EYES: FLUSH ANY SKIN OR EYE CONTACT WITH PLENTY OF WATER.
ADDITIONALLY WITH SKIN CONTACT, WASH WITH SOAP
AND WATER. REFER TO
PHYSICIAN IF IRRITATION OR SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point: 152F, >67C
Spec Gravity: 0.83
Solubility in Water: NEGLIGIBLE
Appearance and Odor: STRAW COLORED LIQUID WITH CHARACTERISTIC SOLVENT
ODOR.
Percent Volatiles by Volume: 75

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products: CARBON
MONOXIDE, CARBON DIOXIDE &
OTHER TOXIC VAPORS & GASES COMMON TO THERMAL DEGRADATION OF ORGANIC
COMPOUNDS.

=====
Disposal Considerations
=====

Waste Disposal Methods: INCINERATION OR OTHER METHOD APPROVED FOR
IGNITABLE WASTES IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United

States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.