

HILLYARD CHEMICAL CO -- FINISH FLOOR NONBUFFING QPL-24685 DECK FINI -- 7930-01-183-9562

=====
Product Identification
=====

Product ID:FINISH FLOOR NONBUFFING QPL-24685 DECK FINI

MSDS Date:04/20/1990

FSC:7930

NIIN:01-183-9562

MSDS Number: BLJNM

=== Responsible Party ===

Company Name:HILLYARD CHEMICAL CO

Address:302 NORTH FOURTH ST

City:ST JOSEPH

State:MO

ZIP:64502

Country:US

Info Phone Num:816-233-

1321

Emergency Phone Num:816-233-1321

CAGE:DO351

=== Contractor Identification ===

Company Name:HILLYARD CHEMICAL CO

Address:302 NORTH FOURTH STREET

City:ST. JOSEPH

State:MO

ZIP:64502

Phone:816-233-1321

CAGE:DO351

Company Name:HILLYARD INDUSTRIES

Address:302 NORTH FOURTH STREET

Box:City:ST JOSEPH

State:MO

ZIP:64501

Country:US

Phone:816-233-1321 (EXT 2303)

CAGE:28745

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENT

=====

Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:CONTACT MAY CAUSE MILD EYE IRRITATION. CHRONIC:NONE KNOWN.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:NONE KNOWN.

Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====
=====

First Aid:EYE:FLUSH W/WATER FOR AT LEAST 15 MINS. IF WEARING CONTACT LENSES, REMOVE & FLUSH AGAIN W/PLENTY OF WATER. IF IRRITATION PERSISTS, GET MD. SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER . INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE OXYGEN/ARTIFICIAL RESPIRATION) . INGEST:CALL MD IMMEDIATELY .

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:NONE

Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE CONDITIONS .

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:MATERIAL MAY SPATTER IF TEMPERATURES EXCEED BOILING POINT. POLYMER FILM CAN BURN.

===== Accidental Release Measures =====

Spill Release Procedures:PICK UP W/MOP OR WET VAC & WASH AWAY W/WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:

PRODUCT SHELF LIFE IS BEST RETAINED BY STORAGE AT 45-100F TEMPERATURES. FREEZING OF PRODUCT MAY RUPTURE CONTAINER.

Other Precautions:INHALATION EXPOSURE TO SPRAY MIST SHOULD BE MAINTAINED AT LESS THAN 10 MG/M3 PER EIGHT HOUR EXPOSURE (TWA LIMIT EST. FOR NUISANCE DUST).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED.

Ventilation:MECHANICAL GENERAL SUGGESTED.

Protective Gloves:NONE REQUIRED.

Eye Protection:CHEMICAL WORK

KERS GOGGLES .

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. WASH CONTAMINATED
CLOTHING BEFORE REUSE.

Supplemental Safety and Health

SPEC GRAV:1.014 @ 102 F; 1.026 @ 68 F

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:210F,99C

Spec Gravity:SEE SUPP DATA

Evaporation Rate & Reference: