

ORGANIC PRODUCTS COMPANY -- F-1000 SENTRY SEAL -- 8030-01-211-9576

===== Product Identification =====

Product ID:F-1000 SENTRY SEAL

MSDS Date:02/26/1988

FSC:8030

NIIN:01-211-9576

MSDS Number: BLJPF

=== Responsible Party ===

Company Name:ORGANIC PRODUCTS COMPANY

Address:1963 E. IRVING BLVD.

City:IRVING

State:TX

ZIP:75060

Country:US

Info Phone Num:214-438-7321

Emergency Phone Num:214-438-7321

CAGE:

01195

=== Contractor Identification ===

Company Name:ORGANIC PRODUCTS CO.

Address:1963 E. IRVING BOULEVARD

Box:428

City:IRVING

State:TX

ZIP:75060-4555

Country:US

Phone:214-438-7321

CAGE:01195

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 60%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METALLIC DRIERS

Fr

action by Wt: .1-.4%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:FATIGUE, HEADACHE, MENTAL CONFUSION,
STRONG DEGREASER OF SKIN. EYE: SEVERE IRRITATION, UNCONSCIOUSNESS,
NAUSEA. IF SWALLOWED, VOMITING.

Effects of Overexposure:FATIGUE, HEADACHE, MENTAL CONFUSION, STRONG
DEGREASER OF SKIN. EYE: SEVERE IRRITATION, UNCONSCIOUSNESS, NAUSEA.
IF SWALLOWED, VOMITING.

=====
First
Aid Measures
=====

First Aid:REMOVE TO FRESH AIR. WASH AND FLUSH AFFECTED AREAS WITH WATER
AND SOAP, FLUSH EYES. DO NOT INDUCE VOMITING IF SWALLOWED, KEEP
WARM AND QUIET. CALL FOR MEDICAL HELP.

=====
Fire Fighting Measures
=====

Flash Point Method:CC

Flash Point:45.0F,7.2C

Extinguishing Media:CARBON DIOXIDE OR DRY CHEMICAL, REGULAR FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A
FULL FACE PIECE WITH
HIGH PRESSURE ON DEMAND.

Unusual Fire/Explosion Hazard:KEEP AWAY FROM PILOT LIGHTS, LIGHTS,
FLAMES, SPARKS, HEATERS, SMOKERS.

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WEAR SUITABLE
PROTECTIVE EQUIPMENT. COLLECT IN A FLAMMABLE WASTE CONTAINER FOR
DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:WEAR RESISTANT GLOVES SUCH AS NITRILE
RUBBER

ER, EYE PROTECTION, CHEMICAL SPLASH GOGGLES AND PROTECTIVE EQUIPMENT TO PREVENT PROLONGED SKIN CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: AIR SUPPLIED MASKS IN CONFINED AREAS, IF LARGE QUANTITIES USED.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE

Protective Gloves: YES, IF LARGE QUANTITIES USED.

Eye Protection: GOGGLES, IF LARGE QUANTITIES USED.

Other Protective Equipment: SAFETY SHOWER AND EYE BATH.

Supplem

ental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC: F3

Boiling Pt: B.P. Text: 230F, 110C

Vapor Pres: 20

Vapor Density: 3.2

Spec Gravity: .87

Evaporation Rate & Reference: 2.4

Solubility in Water: NIL

Appearance and Odor: AROMATIC ODOR, HEAVY THICK PASTE

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: AVOID HEAT, SPARKS, AND FIRES.

=====

=====
===== Disposal Considerations =====

Waste Disposal Methods: DESTROY BY LIQUID INCINERATION. USE ABSORBENT MATERIAL AND DEPOSIT IN TOXIC LANDFILL IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to

be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.