

SUPERBOND, INC. -- SB 709 -- 8040-00-264-3891

=====
Product Identification
=====

Product ID:SB 709
MSDS Date:12/12/1990
FSC:8040
NIIN:00-264-3891
MSDS Number: BLJSX
=== Responsible Party ===
Company Name:SUPERBOND, INC.
Address:3320 COLLINS STREET
Box:14733
City:PHILADELPHIA
State:PA
ZIP:19134
Country:US
Info Phone Num:800-321-0161
Emergency Phone Num:800-321-0161
Preparer's Name:WILLIAM E. FOGG
CAGE:KO968
=== Contractor Identification ===
Company Name:SUPERBOND, INC.
Address:3320 COLLINS STREET
Box:14733
City:PHILADELPHIA
State:PA
ZIP:19134
Country:US
Phone:800-321-0161
CAGE:KO968

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATE
CAS:64742-95-6
Other REC Limits:NONE SPECIFIED
OSHA PEL:25 PPM TWA

Ingred Name:ASPHALT (PETROLEUM)
CAS:8052-42-4
RTECS #:CI9900000
Other REC Limits:NONE SPECIFIED
ACGIH TLV:5 MG/M3; (FUME);9192

=====

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:ACUTE: HEADACHE, DROWSINESS,
DIZZINESS. CHRONIC: PAINTERS SYNDROME.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. SEEK MEDICAL ATTENTION IF
CONDITION PERSISTS. EYES: FLUSH EYES W/CLEAN WATER. SKIN: REMOVE
CONTAMINATED CLOTHING AND CLEANSE SKIN. INGESTION: SEEK MEDICAL
ATTENTION.

=====
Fire Fighting Measu
res
=====

Flash Point Method:COC
Flash Point:104F,40C
Extinguishing Media:CO2 AND DRY CHEMICAL.
Fire Fighting Procedures:TREAT AS OIL FIRE. USE FULL TURNOUT GEAR. USE
SELF-CONTAINED BREATHING APPARATUS FOR FIRES IN CONTAINED AREA.

=====
Accidental Release Measures
=====

Spill Release Procedures:DIKE SPILL AND ABSORB. KEEP OUT OF WATERWAYS
AND SEWERS.

=====
Handling and Storage
=====

Handling and Storage
Precautions:MATERIAL IS COMBUSTIBLE, KEEP AWAY
FROM FLAMES AND SPARKS. DO NOT REUSE EMPTY CONTAINERS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE IF THRESHOLD LIMITS ARE EXCEEDED.
Ventilation:LOCAL EXHAUST.
Protective Gloves:IMPERMEABLE GLOVES.
Eye Protection:SAFETY GLASSES.
Work Hygienic Practices:USE GOOD PERSONAL HYGIENE PRACTICE.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Boili

ng Pt:B.P. Text:310 TO 350F
Vapor Pres:2.7 MM HG
Vapor Density:4.2
Spec Gravity:1.1
Evaporation Rate & Reference:0.37
Solubility in Water:LESS 0.1
Appearance and Odor:BLACK MASTIC W/SOLVENT ODOR.
Percent Volatiles by Volume:13/15

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING CHEMICALS.
Stability Condition to Avoid:ANY SOURCE OF IGNITION.
Hazardous Decomposition Products:OXIDES OF CARBON AND HYDROGEN SULFIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH LOCAL, COUNTY, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.