

UNION OIL CO OF CALIFORNIA -- CARBON DIOXIDE-LIQUID -- 4220-00-920-3651

=====
Product Identification
=====

Product ID:CARBON DIOXIDE-LIQUID

MSDS Date:01/01/1987

FSC:4220

NIIN:00-920-3651

MSDS Number: BLJXV

=== Responsible Party ===

Company Name:UNION OIL CO OF CALIFORNIA

Address:461 S BOYLSTON ST

Box:7600

City:LOS ANGELES

State:CA

ZIP:90017-1443

Country:US

Info Phone Num:213-664-2121, HEALTH INFO

RMATION

Emergency Phone Num:800-424-9300, TRANSPORTATION

CAGE:79003

=== Contractor Identification ===

Company Name:AMERICAN SAFETY FLIGHT SYSTEMS INC

Address:1311 GRAND CENTRAL AVE

Box:City:GLENDALE

State:CA

ZIP:91201-2427

Country:US

Phone:818-240-1080/FAX 241-5296 M.JACKSON

CAGE:31441

Company Name:UNION OIL CO OF CA UNION 76 DIV- WESTERN REGION

Address:1201 W 5TH ST

Box:7600

City:LOS ANGELES

State:CA

ZIP:90017-1443

Country:US

CAGE:79003

=====
Composition/Information on Ingredients
=====

=====

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LIQUID RELEASED TO ATMOSPHERE TURNS TO
SOLID CARBON DIOXIDE (WHICH MAY FREEZE SKIN). GASEOUS CARBON
DIOXID
E (AT 2 TO 3%) IS A SIMPLE ASPHYXICANT.
Effects of Overexposure:ASPHYXIA IN HIGH CONCENTRATIONS. HEADACHE.
DIZZINESS. INCREASE IN HEART RATE AND CARDIAC OUTPUT.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SOLID CARBON DIOXIDE: TREAT FOR FROSTBITE. GASEOUS: REMOVE
FROM EXPOSURE. RECOVERY IS RAPID.

===== Fire Fighting Measures =====

Flash Point:NON-F
LAMMABLE
Extinguishing Media:THIS PRODUCT EXTINGUISHES FIRE.
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE VENTILATION. BEWARE OF THE POSSIBILITY
OF FROSTBITE.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:USE AND STORE THIS PRODUCT WITH
ADEQUATE VENTILATION. AVOID DIRECT CONTACT WITH SKI

N.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS WHEN VAPOR CONCENTRATIONS ARE ABOVE THE TLV.

Ventilation:USE LOCAL EXHAUST VENTILATION.

Protective Gloves:IMPERMEABLE GLOVES.

Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES

Other Protective Equipment:A FACESHIELD MAY BE NECESSARY.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:G3

Vapor Density:> AIR

Spec Gravity:1.101 AT -34.6F

Evaporation Rate & Reference:> ETHER

Appearance and Odor:COLORLESS LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE

Stability Condition to Avoid:DO NOT PUT LIQUID CARBON DIOXIDE IN A LOW PRESSURE TANK OR ONE WITHOUT A RELIEF VALVE.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:BLOW TO ATMOSPHERE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume re

sponsibility for the suitability of this information to their particular situation.