

ZIEBART PRODUCTS GROUP, ZIEBART INTERNATIONAL CORP -- 601605, XL5-G --
8030-01-127-3684

===== Product Identification =====

Product ID:601605, XL5-G

MSDS Date:05/17/1991

FSC:8030

NIIN:01-127-3684

MSDS Number: BLLCQ

=== Responsible Party ===

Company Name:ZIEBART PRODUCTS GROUP, ZIEBART INTERNATIONAL CORP

Address:26500 CAPITOL AVE

City:REDFORD

State:MI

ZIP:48239

Country:US

Info Phone Num:313-947-071

0

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:GORDON POLIQUIN

CAGE:NO002

=== Contractor Identification ===

Company Name:ZIEBART INTERNATIONAL CORP ZIEBART PRODUCTS GROUP

Address:26500 CAPITOL AVE

Box:City:REDFORD

State:MI

ZIP:48239-2506

Country:US

CAGE:4W458

Company Name:ZIEBART PRODUCTS GROUP, DIV OF ZIEBART INT'L CORP

Address:26500 CAPITOL AVE

City:REDFORD

State:MI

ZIP:48239

Country:US

Phone:313-937-0710 (8 AM-5 PM, M-F)

CAGE:NO002

===== Composition/Information on Ingre

dients =====

Ingred Name:PETROLEUM DISTILLATES
CAS:64742-53-6
RTECS #:PY8036000
Fraction by Wt: 3%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 42%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

Ingred Name:VOC: 2.91 LB/GAL (NO H2O)
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====
=

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SYMPTOMS RANGE FROM MILD
DEPRESSION TO CONVULSIONS AND LOSS OF CONSCIOUSNESS. SKIN CONTACT
CAUSES IRRITATION. CHRONIC: SKIN CONTACT CAUSES IRRITATION,
DEFATTING & DERMATITIS.
Effects of Overexposure:SKIN: IRRITATION/RASH. INGESTION: VOMITING,
DIARRHEA AND GASTROINTESTINAL PAIN. INHALATION: NAUSEA, SHORTNESS
OF BREATH, DIZZINE
SS.
Medical Cond Aggravated by Exposure:SKIN, LIVER, KIDNEY AND C.N.S.
DISORDERS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR, GIVE OXYGEN, CONTACT
PHYSICIAN. EYES: FLUSH WITH WATER. CONTACT PHYSICIAN. SKIN: REMOVE
CONTAMINATED CLOTHING, WASH WITH WATER. INGESTION: DO NOT INDUCE
VOMITING, CONTACT PHYSICIAN; GIVE WHITE MINERAL OIL.

===== Fire Fighting Measures =====

Flash Poin

t Method:PMCC

Flash Point:101F,38C

Autoignition Temp:Autoignition Temp Text:800 F

Lower Limits:0.8

Upper Limits:6.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS. REMOVE ALL SOURCES OF IGNITION.

Unusual Fire/Explosion Hazard:PETROLEUM DISTILLATES ARE A FIRE AND EXPLOSION HAZARD. VAPORS CAN FLOW TO DISTANT IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:RE

MOVE SOURCES OF IGNITION, PROVIDE ADEQUATE VENTILATION, ABSORB WITH VERMICULITE OR OTHER ABSORBENT. SPILLED MATERIAL IS A HAZARDOUS WASTE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION.

Other Precautions:PREVENT SKIN CONTACT AND AVOID BREATHING VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AIR PURIFYING R

ESPIRATOR WITH ORGANIC VAPOR

CARTRIDGE AT >TLV. USE SCBA AT >10 TIMES THE TLV.

Ventilation:LOCAL EXHAUST RECOMMENDED. MAINTAIN ADEQUATE TRANSFER

VELOCITY TO PREVENT EXPLOSIVE CONC. ELIMINATE IGNITION SOURCES.

Protective Gloves:USE BUNA-N-RUBBER GLOVES.

Eye Protection:GOGGLES OR FACE SHIELDS RECOMMENDED.

Other Protective Equipment:USE BUNA-N-RUBBER APRON.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>350F

,>177C
Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C
Decomp Temp:Decomp Text:800F,427C
Vapor Pres:10
Vapor Density:4.8 @ 68 F
Spec Gravity:0.888
pH:7
Viscosity:*
Evaporation Rate & Reference:0.2 (BUAC = 1)
Solubility in Water:SLIGHT
Appearance and Odor:BLACK LIQUID WITH MILD ODOR.
Percent Volatiles by Volume:45.31

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, FLAME AND HEAT (200 F MAX). NONCORROSIVE TO
M
ETAL.
Hazardous Decomposition Products:OXIDES OF CARBON, NITROGEN AND SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS EPA HAZARDOUS WASTE NUMBER D001 BY
INCINERATION OR STABILIZATION AT AN EPA LICENSED FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.