

SPEDE TOOL MANUFACTURING INC. -- CUT-OFF WHEELS, RESINOID -- 3460-01-009-0349

=====  
Product Identification  
=====

Product ID:CUT-OFF WHEELS, RESINOID  
MSDS Date:01/05/1991  
FSC:3460  
NIIN:01-009-0349  
MSDS Number: BLLWT  
=== Responsible Party ===  
Company Name:SPEDE TOOL MANUFACTURING INC.  
Address:10042 RANCHO RD  
Box:40  
City:ADELANTO  
State:CA  
ZIP:92301-0040  
Country:US  
Info Phone Num:619-246-6850  
Emergenc  
y Phone Num:800-423-4836  
Preparer's Name:WAYNE PARKER  
CAGE:JO135

==== Contractor Identification ====

Company Name:SPEDE TOOL MANUFACTURING ING  
Address:10042 RANCHO ROAD  
Box:40  
City:ADELANTO  
State:CA  
ZIP:92301  
Country:US  
Phone:619-246-6850  
CAGE:JO135  
Company Name:SPEDE TOOL MFG CO INC  
Address:10042 RANCHO RD  
Box:40  
City:ADELANTO  
State:CA  
ZIP:92301-0040  
Country:US  
CAGE:56268

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LIQUID PHENOLIC RESIN-8121  
Fraction by Wt: 0

.01%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:1 PPM  
ACGIH TLV:3 PPM

Ingred Name:PHENOL FORMALDEHYDE SYNTHETIC RESIN POWDER  
Fraction by Wt: 15%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:5 PPM

Ingred Name:CRYOLITE 98%, SODIUM HEXAFLUORO-ALUMINATE  
CAS:15096-52-3  
Fraction by Wt: 0.07%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:2.5 MG/M3 AS F

Ingred Name:ALUMINUM OXIDE GRAIN ALUMINA  
Fraction by Wt: 80%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:20 MG/M3 NUIS. DUST

Ingred Name:PHENOLIC PREPREG FIBERGLASS  
Fraction by Wt: 0.02%  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: OVEREXPOSURE TO DUST WILL CAUSE  
SKIN AND RESPIRATORY TRACT IRRITATION. A RESPIRATOR MAY BE  
REQUIRED. IF INGESTED, GASTROINTESTINAL DISTURBANCES, NAUSEA, AND  
VOMITING MAY RESULT.  
Explanation of Carcinogenicity:N  
ONE OF THE COMPOUNDS IN THIS PRODUCT IS  
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.  
Effects of Overexposure:RASH, IRRITATION OR REDNESS.  
Medical Cond Aggravated by Exposure:PRODUCT CAN CAUSE SERIOUS PHYSICAL  
BODILY INJURY IF GUARDS AND PROTECTIVE COVERING ARE NOT USED.

=====  
===== First Aid Measures =====

First Aid:FLUSH EYES WITH CLEAN WATER FOR 15 MINUTES AND WASH ARMS,  
FACE AND LEGS WITH SOAP AND WATER. CONSULT A PHYSICIAN.

=====

= Fire Fighting Measures =====

Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:PICK OR SWEEP UP. GRINDING OR CUT OFF WHEELS IF DROPPED OR DAMAGED CAN CAUSE SERIOUS BOKILY INJURY. AVOID USAGE IF PRODUC

T HAS BEEN DROPPED OR FALLEN.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLE CAREFULLY. WHEELS SHALL NOT BE STORED SUBJECT TO WATER OR SOLVENTS, HIGH HUMIDITY OR FREEZING TEMPERATURES.

Other Precautions:COMPLY WITH ANSI B7.1 SAFETY, USE CARE OF ABRASIVE WHEELS. COMPLY WITH RPM RATING OF EACH PRODUCT.

===== Exposure Controls/Personal Protection =====

Respiratory Protec

tion:IF VENTILATION DOES NOT MAINTAIN INHALATION

EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE AND DUST/MIST PRE-FILTER RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/ WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:SPARK PROOF

Eye Protection:FACE SHIELD

Other Protective Equipment:SAFETY SHOES, FIRE PRO OF CLOTHING, AND HEAD PROTECTION.

Work Hygienic Practices:KEEP DUST WASHED OFF SKIN, WEAR CLEAN CLOTHING.

Supplemental Safety and Health

AVOID CONTACT WITH SPARKS. DO NOT WEAR CONTACT LENSES.

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:900F,482C

Spec Gravity:2.0

Solubility in Water:SLIGHT

Appearance and Odor:DARK BROWN TO BLACK COLOR, SLIGHT PHENOLIC ODOR WHILE GRINDING.

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

CHLORINE TRIFLUORIDE, WATER, ALCOHOLS OR POLYALS.

Stability Condition to Avoid: AVOID USAGE IN CLOSED OR CONFINED AREAS.

Hazardous Decomposition Products: AVOID EXTREME HEAT AND COLD STORAGE.

===== Disposal Considerations =====

Waste Disposal Methods: SANITARY LANDFILL OR INCINERATION IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.