

EVERSEAL MFG CO INC -- YELLOW GLOSS ALKYD ENAMEL -- 8010-00-584-3081

=====
Product Identification
=====

Product ID:YELLOW GLOSS ALKYD ENAMEL

MSDS Date:03/14/1986

FSC:8010

NIIN:00-584-3081

MSDS Number: BLNFJ

=== Responsible Party ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

City:RIDGFIELD

State:NJ

ZIP:07657

Country:US

Info Phone Num:201-943-4986

Emergency Phone Num:201-943-4986

CAGE:

72988

=== Contractor Identification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

=====
Composition/Information on Ingredients
=====

Ingred Name:RESIN

Fraction by Wt: 30%

Other REC Limits:NONE SPECIFIED

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 2%

Other REC Limits:15 MG/M3 DUST

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Nam

e:LEAD CHROMATE (AS PB, CR) (SARA 313)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: (18, 4%)

Other REC Limits:0.5 MG/M3 DUST

Ingred Name:MINERAL SPIRITS (VP: 2 MM HG)

Fraction by Wt: 38%

Other REC Limits:120 PPM

=====
===== Hazards Identification =====

LD50 LC50 Mixture:5 G/KG (ORAL)-MINERAL SPIRITS

Health Hazards Acute and Chronic:INHALATION MAY CAUSE DIZZINESS, NAUSEA
OR IN EXTREME CASES UNCONSCIOUSNESS.

=====
===== First Aid Measures =====

First Aid:INHALE: REMOVE TO FRESH AIR. INGEST: DO NOT INDUCE VOMITING,
CALL PHYSICIAN. UNCONSCIOUSNESS: CALL PHYSICIAN, EFFECT OXYGEN
RESUSCITATION.

=====
===== Fire Fighting Measures =====

Flash Point:105F,41C

Lower Limits:0.7

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING MEDIUM

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMO

VE ANY IGNITION SOURCES. ENSURE ADEQUATE
VENTIALATION. ABSORB ON DRY ABSORBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM IGNITION SOURCES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:VAPOR, FUME, DUST CANISTER MASK

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENSURE LEL NOT ACHIEVED.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Supplemental Safety and Health

=====

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:326 TO 387F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS

Hazardous Decomposition Products:CARBON MONOXIDE IN CASES OF INCOMPLETE
COMBUSTION

===== Disposal Considerations =====

=

Waste Disposal Methods:DISPOSE OF AS PER LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.