

REXSELLIX LABRATORIES, INC. -- ANTI-FOGGING COMPOUND -- 6850-00-754-2672

=====
Product Identification
=====

Product ID:ANTI-FOGGING COMPOUND

MSDS Date:07/01/1990

FSC:6850

NIIN:00-754-2672

MSDS Number: BLNFT

=== Responsible Party ===

Company Name:REXSELLIX LABRATORIES, INC.

Box:426

City:CAMDEN

State:TN

ZIP:38320

Country:US

Info Phone Num:901-584-7860

Emergency Phone Num:800-424-9300 CHEMTREC

Prepa

er's Name:JACK BEAUCHAMP

CAGE:LO904

=== Contractor Identification ===

Company Name:REXSELLIX LABORATORIES, INC.

Box:City:CAMDEN

State:TN

ZIP:38320

Country:US

Phone:901-584-7860

CAGE:9J970

Company Name:REXSELLIX LABRATORIES, INC.

Box:426

City:CAMDEN

State:TN

ZIP:38320

Country:US

Phone:901-584-7860

CAGE:LO904

=====
Composition/Information on Ingredients
=====

Ingred Name:NONHAZARDOUS INGREDIENTS

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification ==

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. CAN CAUSE
SERIOUS NERVOUS SYSTEM DEPRESSION.
Effects of Overexposure:INHALATION: IRRITATES RESPIRATORY TRACT. SKIN:
PRIMARY IRRITATION TO SKIN, DEFATTING & DERMATITIS. EYES:
IRRITATION TO EYES, REDNESS, TEARING, BLURRED VISION. SWALLOWING:
SWALLOWING CAN CAUSE ABDOMINAL IRRITATION, NAUSEA, VOMITING &
DIARRHEA.

===== First Aid Measures =====

First Aid:SKIN: FLUSH W/PLENTY OF WATER. EYES: FLUSH W/PLENTY OF WATER
FOR 15 MINUTES. GET MED ATTN. AFTER HIGH VAPOR EXPOSURE, REMOVE TO
FRESH AIR. IF BREATHING IS DIFFICULT GIVE OXYGEN. IF BREATHING HAS
STOPPED GIVE CPR. SWALLOW: CALL PHYSICIAN IMMEDIATELY. INDUCE
VOMITING PROMPTLY FOLLOW PHYSICIAN'S INSTRUCTIONS OR BY HAVING
PATIENT STICK FINGER DOWN THROAT. NOTHING BY MOUTH TO UNCONSCIOUS
PERSON.

===== Fire Fighting Measures =====

Extinguishing Media:NFPA CLASS B EXTINGUISHER (CO2 OR FOAM) FOR CLASS
III B LIQUID FIRES.
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE BUT USED TO
COOL CLOSED CONTAINER. USE FOG NOZZLE. WEAR FULL BUNKER GEAR. USE
APPROVED POSITIVE-PRESSURE SCBA.
Unusual Fire/Explosion Hazard:KEEP CNTNR TIGHTLY CLOSED. ISOLATE FROM
OXIDIZERS, HEAT, OPEN FLAME. CLOSED CNTNR MAY EXPLODE FROM EXTREME
HEAT. HOT SURFACE APPLICATION REQUIRES PRECAUTIONS.

===== Accidental Release Measures =====

Spill Release Procedures:STOP SPILL AT SOURCE. DIKE AREA & CONTAIN.
PUMP SPILLED LIQUID & PUT CONTAMINATED SOIL IN DOT APPROVED
CONTAINER FOR DISPOSAL. LABEL IMMEDIATELY. CLEAN UP REMAINDER WITH
ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 49C/120F. STORE
LA

RGE AMOUNTS IN STRUCTURES MADE FOR OSHA CLASS III B LIQUIDS.

AVOID FREE FALL OF LIQUIDS.

Other Precautions:GROUND CONTAINERS WHEN TRANSFERRING. DO NOT FLAME CUT, BRAZE OR WELD. EMPTY CONTAINER VERY HAZARDOUS. CONTINUE ALL LABEL PRECAUTIONS.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST: NECESSARY. MECHANICAL (GENERAL): ACCEPTABLE.

Protective Gloves:WEAR IMPERVIOUS GLOVES.

Eye Protection:WEAR GOGGLES OR FACE SHIELD.

Other Protective Eq

uipment:WEAR GLOVES, APRON & FOOTWEAR IMPERVIOUS TO THIS MATERIAL.

Work Hygienic Practices:WASH CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:15.8

Vapor Density:0.6

Spec Gravity:1.0 (WATER=1)

Appearance and Odor:LIQUID, WATER-WHITE

Percent Volatiles by Volume:80.0

===== Stability and Reactivity Data =====

=

Stability Indicator/Materials to Avoid:YES

ISOLATE FROM STRONG OXIDIZERS SUCH AS PERMANGANATES, CHROMATES & PEROXIDES.

Stability Condition to Avoid:ISOLATE FROM OXIDIZERS, HEAT AND OPEN FLAMES.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, SILICON DIOXIDE FROM BURNING.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE BY LEGAL METHODS. COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS. IF QUESTIONS

EXIST, CONTACT
THE APPROPRIATE AGENCIES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.