

MALLINCKRODT INC SCIENCE PROD DIV -- SODIUM DICHROMATE -- 6810-00-312-7158

=====
Product Identification
=====

Product ID:SODIUM DICHROMATE

MSDS Date:04/06/1989

FSC:6810

NIIN:00-312-7158

MSDS Number: BLPFH

=== Responsible Party ===

Company Name:MALLINCKRODT INC SCIENCE PROD DIV

Box:M

City:PARIS

State:KY

ZIP:43061

Country:US

Info Phone Num:314-982-5000

Emergency Phone Num:314-982-5000

CAGE:62910

===

Contractor Identification ===

Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

=====
Composition/Information on Ingredients
=====

Ingred Name:DICHROMIC ACID (H*2CR*2O*7), DISODIUM SALT, DIHYDRATE;
(SODIUM DICHROMATE)

CAS:7789-12-0

RTECS #:HX7750000

OSHA PEL:0.1 MG(CRO*3)/M3

ACGIH TLV:0.05 MG(CR)/M3

Ingred Name:SUPP DATA:SODA LIME. DISPOSE OF SOLIDS AS HAZ WASTE

IN RCRA

APPRVD FACILITY. ENSURE COMPLIANCE W/LOCAL,STATE & FED REGS.

RTECS #:9999999ZZ

Ingred Name:OTHER PREC:GARMENTS AT END OF DAY.AVOID CROSS- CONTAM OF STREET CLOTHES.KEEP FROM CNTCT W/CLTHG,OTHER COMBUST(SEE ING 4)

RTECS #:9999999ZZ

Ingred Name:ING 3:MATLS. DO NOT STORE NEAR COMBUST MATLS. STORE IN TIGHTLY CLOSED CNTNR. REMOVE & WASH CONTAMD CLTHG (SEE ING 5)

RTECS #:9999999ZZ

Ingred Name:ING 4:IMMED.USE ONLY W/ADEQ VENT.DO NOT BREATHE DUST.DO NOT GET IN EYES,ON SKIN/CLTH

G.CNTCT W/OTHER MATL MAY CAUSE FIRE.

RTECS #:9999999ZZ

Ingred Name:HYGIENE PRACT:OR SMOKE IN WORKPLACE. WASH THOROUGHLY AFTER HANDLING.

RTECS #:9999999ZZ

Ingred Name:VENT:BECAUSE IT CAN CONTROL EMISSIONS OF CONTAMINANT AT SOURCE, PREVENTING DISPERSION INTO GENERAL WORK AREA.

RTECS #:9999999ZZ

Ingred Name:EFTS OF OVEREXP:DANGER! POWERFUL OXIDIZER. CAUSES SEVERE BURNS. MAY CAUSE DELAYED BURNS OR EXTERNAL ULCERS. (SEE ING 9)

RTECS #:9999999ZZ

Ingred Name:ING 8:CONTAINS HEXAVALENT CHROMIUM. EXPOSURE MAY CREATE A

CANCER RISK. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED.

RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:LD50:(ORAL,RAT)50 MG/KG.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:INHAL:SEVERE IRRITANT. CORR ACTION ON MUC MEMB & RESP TRACT MAY PRDCE NASAL IRRIT & BURNING SENSATION IN THROAT. INGEST:T

OXIC. CORR TO MOUTH & GI TRACT. SYMPS MAY INCLUDE
ABDOMINAL PAIN, DIZZ, VOMIT, INTENSE THIRST, SHOCK & KIDNEY
FAILURE.FATAL DOSE MAY BE AS LOW AS 5 GRAMS. SKIN:CORR. MAY PRDCE
(SEE EFTS OF OVEREXP)

Explanation of Carcinogenicity:SODIUM DICHROMATE:GROUP 1 (NTP); IARC -
GROUP 1

Effects of Overexposure:HLTH HAZ:SKIN RASHES & ULCERS. BICHROMATES ARE
SKIN SENSITIZERS. EYE:CORR. MAY CAUSE CONJUNCT IF IN CNTCT W/EYES.
CHRONIC:RPTD SKIN CNTCT MAY LEAD TO INCAPACITATING DERM & SL

OW
HEALING ULCERS. RPTD IN HAL MAY CAUSE PERFORATION OF NASAL SEPTUM.
BICHROMATES PRIMARILY TOXIC TO KIDNEYS, LIVER & GI TRACT. (SEE ING
8)

Medical Cond Aggravated by Exposure:PERSONS W/PRE-EXISTING SKIN OR EYE
PROBLEMS OR IMPAIRED LIVER, KIDNEY OR RESPIRATORY FUNCTION MAY BE
MORE SUSCEPTIBLE TO EFFECTS OF THIS SUBSTANCE.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. IF NOT BRTHG, GIVE ARTF RESP. IF
BRTHG DFCLT
, GIVE O*2. CALL MD. INGEST: INDUCE VOMIT IMMED BY
GIVING 2 GLASSES OF WATER & STICKING FINGER DOWN THROAT. NEVER GIVE
ANYTHING B Y MOUTH TO UNCON PERSON. CALL MD IMMED.SKIN:REMOVE ANY
CONTAMD CLTHG. WIPE OFF EXCESS FROM SKIN. WASH W/PLENTY OF WATER
FOR AT LEAST 15 MIN.GET MD IMMED. EYE:WASH W/PLENTY OF WATER FOR AT
(SUPP DATA)

===== Fire Fighting Measures =====

Flash Point:NOT COMBUSTIBLE

Extinguishing Media:USE ANY MEANS SUITABLE FOR EXTI
NGUISHING

SURROUNDING FIRE. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED
CONTAINERS COOL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP
. NOT COMBUSTIBLE, BUT SUBSTANCE IS STRONG OXIDIZER & HEAT OF RXN
W/REDUCING AGENTS/COMBUST MAY CAUSE IGNIT.

Unusual Fire/Explosion Hazard:STRONG OXIDANTS MAY EXPLODE WHEN
SHOCKED/IF EXPOSED TO HEAT, FLAME/FRICTION. ALSO MAY ACT AS
INITIATION SOURCE FOR DUST OR VAPOR EXPLOSIONS.

===== Accidental Rel

CHROMIUM MAY THEN BE PRECIPITATED AS HYDROUSCHROMIC OXIDE BY NEUTRALIZING TO PH 7.5 W/SODA ASH, CAUSTIC SODA OR (SEE ING 2)

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:SUPP DATA

Melt/Freeze Pt:M.P/F.P Text:675F,357C

Vapor Pres:0 @ 68F

Spec Gravity:2.35 @ 77F

Solubility in Water:SOLUBLE (73%)

Appearance and Odor:ORANGE-RED CRYSTALS OR GRANULES, ODORLESS.

===== Stability and Reactivity Data =====

Stability Indicator/

Materials to Avoid:YES

HYDRAZINE, ACETIC ANHYDRIDE, ETHANOL, TRINITROTOLUENE, HYDROXYLAMINE, STRONG ACIDS, OXIDIZABLE MATERIALS (SUPP DATA)

Stability Condition to Avoid:STABLE UNDER ORDINARY CONDITIONS OF USE AND STORAGE.

Hazardous Decomposition Products:OXIDES OF CHROMIUM.

===== Disposal Considerations =====

Waste Disposal Methods:CONTAINERIZED SOLIDS MAY BE SENT TO RCRA APPROVED HAZ WASTE DISP FACILITY. HEXAVALENT CHROMIUM IN SOLN MAY BE REDUCED

TO TRIVALENT CHROMIUM BY A VARIETY OF REDUCING AGENTS SUCH AS SODIUM BISULFITE, SODIUM SULFITE, SULFUR DIOXIDE OR FERROUS (SUPP DATA)

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should

seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.