

HANDY AND HARTMAN -- FLUX,AMS 3410 G,0-F-499 D,TYPE B,AWS CLASS -- 3439-00-582-1110
===== Product Identification =====

Product ID:FLUX,AMS 3410 G,0-F-499 D,TYPE B,AWS CLASS

MSDS Date:01/16/1989

FSC:3439

NIIN:00-582-1110

MSDS Number: BLPFQ

=== Responsible Party ===

Company Name:HANDY AND HARTMAN

Address:850 THIRD AVE

City:NEW YORK

State:NY

ZIP:10022-6222

Country:US

Info Phone Num:212-752-3400/203-2

59-8321

Emergency Phone Num:212-207-2632/203-259-8321

CAGE:JO825

=== Contractor Identification ===

Company Name:HANDY & HARMAN

Address:850 THIRD AVENUE

Box:City:NEW YORK

State:NY

ZIP:10022

Country:US

Phone:212-752-3400

CAGE:73977

Company Name:HANDY AND HARTMAN

Address:850 THIRD AVE

City:NEW YORK

State:NY

ZIP:10022-6222

Country:US

Phone:212-752-3400

CAGE:JO825

===== Composition/Information on Ingredients =====

Ingred Name:POTASSIUM FLUORIDE BORATE HYDROXIDE

CAS:12228-71-6

Frac

tion by Wt: 50 - 70%
Other REC Limits:NONE SPECIFIED
OSHA PEL:2.5 MG/M3 (MFR)
ACGIH TLV:2.5 MG/M3 (MFR)

Ingred Name:POTASSIUM HYDROXIDE (SARA III)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 0.05-.9%
Other REC Limits:NONE SPECIFIED
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:POTASSIUM FLUORIDE SOLUTION
CAS:7789-23-3
RTECS #:TT0700000
Fraction by Wt: 5 - 20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:2.5 MG/M3 (MFR)
ACGIH TLV:2.5 MG/M3
(MFR)

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 20 - 35%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 245 MG/KG FLUORIDES
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-FLUORIDES ARE POISONOUS IF
SWALLOWED.POTASSIUM HYDROXIDE IS B
OTH TOXIC(LD50,RAT=365 MG/KG) &
AN IRRITANT.PROLONGED SKIN CONTACT MAY CAUSE
DERMATITIS.OVEREXPOSURE TO BF3 & HF GASES ON HEATING ARE
TOXIC.B2O3 IS AN IRRITANT.CHRONIC-DERMATITIS.
Effects of Overexposure:EYES, SKIN AND RESPIRATORY TRACT IRRITATION.
TOXIC IF SWALLOWED OR INHALED.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE
AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

===== First Aid Measures =====

First Aid:CALL A

PHYSICIAN IN ALL CASES. INHALATION: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEEDED. EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. SKIN: WASH WITH WATER. INGESTION: IF CONSCIOUS, INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point: NONE
Extinguishing Media: WATER
Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS OPERATED IN POSITIVE PRESSURE MODE.
USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures: AVOID CONTACT WITH EYES OR SKIN. AVOID HIGH TEMPERATURES. WEAR RUBBER GLOVES DURING SPILL CLEAN-UP. DILUTE AND WASH SPILLAGE WITH WATER.
Neutralizing Agent: LIME THEN MAGNESIUM HYDROXIDE/ALUMINUM SULFATE

===== Handling and Storage =====

Handling and Storage Precautions: STORAGE-STORE IN A DRY PLACE. AVOID HEATING ABOVE 1050F.
Other Precautions: THIS FLUX IS OFTEN USED WITH BRAZING FILLER METALS CONTAINING CD. CD OXIDE FUMES IS A GREATER HAZARD THAN FLUORIDE FUME FROM FLUX. ZN OXIDE FUME MAY ALSO BE EMITTED. PRODUCTS OF COMBUSTION FROM TORCH/FURNACE MAY BE TOXIC NO₂, O₃ & CO GASES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE FOR BRAZING IN PROPERLY VENTILATED AREA. IN CONFINED SPACE USE AN AIRLINE RESPIRATOR OR HOSE MASK, NIOSH/MSHA APPROVED HOSE TYPE C OR SELF-CONTAINED AIR RESPIRATOR.
Ventilation: LOCAL EXHAUST/MECHANICAL
Protective Gloves: LEATHER WELDING
Eye Protection: SAFETY GOGGLES
Other Protective Equipment: NON-FLAMMABLE PROTECTIVE CLOTHING, PLASTIC FRAME SAFETY SPECTACLES WITH SIDE SHIELDS-FILTER LENSES SHADE # 3 OR # 4
Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.
Su

pplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:1050F,566C

Spec Gravity:1.67

pH:8.5

Solubility in Water:SOLUBLE

Appearance and Odor:WHITE PASTE - NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN

Stability Condition to Avoid:HIGH TEMPERATURES AND OPEN FLAMES

Hazardous Decomposition Products:EXCESSIVE FUMES (BF₃)

=====

===== Disposal Considerations =====

Waste Disposal Methods:ALL EFFLUENT INGREDIENTS ARE INORGANIC. LOCAL REGULATIONS MAY REQUIRE THE REMOVAL OF FLUORIDES AND SUSPENDED TRACE METALS BEFORE DISCHARGE OF FINAL EFFLUENT. ADDITION OF LIME FOLLOWED BY MG(OH)₂/AL₂(S O₄)₃, THEN FILTRATION IS A SIMPLE METHOD.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United S

tates of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.