

UNION CARBIDE CORP/LINDE DIV -- L-4638-A OXYGEN -- 6505-00-132-5225

===== Product Identification =====

Product ID:L-4638-A OXYGEN

MSDS Date:09/01/1985

FSC:6505

NIIN:00-132-5225

MSDS Number: BLRDC

=== Responsible Party ===

Company Name:UNION CARBIDE CORP/LINDE DIV

Address:39 OLD RIDGEBURY ROAD

City:DANBURY

State:CT

ZIP:06817-0001

Info Phone Num:(304) 744-3487

Emergency Phone Num:(304) 744-3487

CAGE

:61637

=== Contractor Identification ===

Company Name:UNION CARBIDE CORP

Address:39 OLD RIDGEBURY ROAD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357/732-563-5522 (MSDS)

CAGE:61637

===== Composition/Information on Ingredients =====

Ingred Name:OXYGEN (GAS)

CAS:7782-44-7

RTECS #:RS2060000

Fraction by Wt: 100%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinoge

nicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: NASAL

STUFFINESS/COUGH/SORE THROAT/CHEST PAIN/BREATHING DIFFICULTY/LUNG
DAMAGE/CNS EFFECTS RESULTING IN DIZZINESS/POOR
COORDINATION/TINGLING SENSATION/VISUAL & HEARING
DISTURBANCES/MUSCULAR
Twitching/unconsciousness/convulsions/prolongation of adaptation to
darkness/reduced peripheral vision.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: ALVEOLAR COLLAPSE FOLLOWING OXY
GEN

absorption, eardrum retraction, obstruction of paranasal sinuses
producing vacuum-type headache. newborn premature infants or adults
exposed to 100% oxygen may suffer delayed retinal damage, which
can progress to retinal detachment & blindness.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION
IF NOT BREATHING. KEEP VICTIM WARM & AT REST. OBTAIN MEDICAL
ATTENTION IN ALL CASES.

PHYSICIAN NOTE: SUPPORTIVE TREATMENT SHOULD
INCLUDE IMMEDIATE SEDATION/ANTI-CONVULSIVE THERAPY/REST. ALL
INDIVIDUALS EXPOSED FOR LONG PERIODS TO OXYGEN AT HIGH PRESSURE &
ALL WHO EXHIBIT OVERT OXYGEN TOXICITY SHOULD HAVE OPHTHALMOLOGIC
EXAMINATIONS.

=====
===== Fire Fighting Measures =====

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. WATER
IS THE PREFERRED EXTINGUISHING MEDIA FOR CLOTHING FIRES.

Fire Fighting Procedures:EVACU

ATE ALL PERSONNEL FROM DANGER AREA. COOL
CONTAINERS W/WATER SPRAY FROM MAXIMUM DISTANCE UNTIL COOL, THEN
MOVE CONTAINERS AWAY FROM FIRE AREA SAFELY.

Unusual Fire/Explosion Hazard:CONTACT W/FLAMMABLE MATERIAL MAY CAUSE
FIRE/EXPLOSION. CONTAINER MAY RUPTURE DUE TO HEAT OF FIRE OR
REVERSE FLOW INTO CYLINDER. COMBUSTIBLE/HIGH PRESSURE GAS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF LEAK IF W/OUT RISK. VENTILATE AREA OF

LEAK OR MOVE LEAKING CONTAINER TO WELL-VENTILATED AREA. REMOVE ALL FLAMMABLE MATERIALS FROM VICINITY. IF THERE IS A LEAK, CLOSE CYLINDER VALVE/BLOW DOWN SYSTEM BY VENTING TO SAFE PLACE/REPAIR THE LEAK.

=====
===== Handling and Storage =====

Handling and Storage Precautions:NEVER LUBRICATE OXYGEN VALVES/REGULATORS/ETC. W/ANY COMBUSTIBLE SUBSTANCE. DON'T USE OXYGEN JET TO CLEAN, INCREASES DANGER OF ENGULFING FIRE.
Other Precautions:USE ONLY W/EQUIPMENT CONDITIONED FOR OXYGEN SERVICE.
OXYGEN MUST NEVER BE PERMITTED TO STRIKE AN OILY SURFACE/GREASY CLOTHES/OTHER COMBUSTIBLE MATERIAL. ISOLATE FROM IGNITION SOURCES. USE CHECK VALVE IN ANY LINE OF PIPING FROM CYLINDER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AS REQUIRED
Ventilation:MECHANICAL (GENERAL): ACCEPTABLE.
Protective Gloves:PREFERRED FOR CYLINDER HANDLING
Eye Protection:AS REQUIRED
Other Protective Equipment:SAFETY SHOWER & METATARSAL SHOES FOR CYLINDER HANDLING
Supplemental Safety and Health
WHEN 2 OR MORE GASES OR LIQUEFIED GASES ARE MIXED, THEIR HAZARDOUS PROPERTIES MAY COMBINE TO CREATE ADDITIONAL UNEXPECTED HAZARDS. READ/UNDERSTAND LABEL PRECAUTION/SAFETY INFORMATION BEFORE PRODUCING MIXTURE. MOST CONTAINERS ARE PROVIDED W/PRESSURE RELIEF DEVICE DESIGNED TO VENT CONTENTS WHEN EXPOSED TO HIGH TEMP.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P.
Text:-297.4F
Melt/Freeze Pt:M.P/F.P Text:-361.1F
Vapor Pres:GAS
Vapor Density:1.105
Spec Gravity:GAS
Solubility in Water:NEGLIGIBLE
Appearance and Odor:COLORLESS, ODORLESS GAS
Percent Volatiles by Volume:100%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS, COMBUSTIBLE MATERIALS, ASPHALT, FLAMMABLE MATERIALS, ESPECIALLY OILS & GREASES
Stability Condition to Avoid:TEMPERATURE >125F, FLAMES, ELECTRIC SPARKS,

PHYSICAL DAMAGE, OVER-HEATING

===== Disposal Considerations =====

Waste Disposal Methods: SLOWLY RELEASE INTO ATMOSPHERE, IN AN OPEN, OUTDOORS AREA IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. COMBUSTIBLE, HIGH PRESSURE GAS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.