View NSN Online: https://aerobasegroup.com/nsn/6830-01-250-2888 NATIONAL WELDERS SUPPLY CO INC -- NITROGEN -- 6830-01-250-2888 ============= Product Identification ======================== Product ID:NITROGEN MSDS Date:01/01/1991 FSC:6830 NIIN:01-250-2888 MSDS Number: BLSTJ === Responsible Party === Company Name: NATIONAL WELDERS SUPPLY CO INC Address:810 GESCO Box:31007 City:CHARLOTTE State:NC ZIP:28231 Country:US Info Phone Num:704-333-5475 Emergency Phone Num:704-333-5475/FAX 72-1-70 4-344-1711 CAGE:18264 === Contractor Identification === Company Name: NATIONAL WELDERS SUPPLY CO INC Address:810 GESCO ST Box:31007 City:CHARLOTTE State:NC ZIP:28231 Country:US Phone:704-333-5475 CAGE:18264 ======= Composition/Information on Ingredients ========

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000 Fraction by Wt: 99.5%

Other REC Limits:NONE SPECIFIED ACGIH TLV:ASPHYXIANT; 9192

========== Hazards Identification =================

Routes of Entry: I

nhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-INHALED:SIMPLE ASPHYXIANT.MAY CAUSE DIZZINESS,TINGLING SENSATIONS,INCOORDINATION,REDUCED CONSCIOUSNESS OF THE SURROUNDINGS,WEEKEND SPEECH,RAPID REDUCTION IN THE ABILITY TO PERFORM MOVEMENTS,TIGH TNESS IN THE FRONTAL AREA OF THE FOREHEAD,HEIGHTENED MENTAL ACTIVITY.CHRONIC-NONE KNOWN.
Effects of Overexposure:MAY CAUSE DIZZINESS, TINGLING SENSATIONS,
NCOORDINATION, REDUCED CONSCIOUSNESS OF THE SURROUNDINGS, WEEKEND SPEECH, RAPID REDUCTION IN THE ABILITY TO PERFORM MOVEMENTS, TIGHTNESS IN THE FRONTAL AREA OF THE FOREHEAD, HEIGHTENED MENTAL ACTIVITY.
Medical Cond Aggravated by Exposure:NONE KNOWN.
======================================
First Aid:PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE TO NITROGEN.RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APP ARATUS. INHALATION:CONSCIOUS PERSONS SHOULD BE ASSIS TED TO AN UNCONTAMINATED AREA AND INHALE FRESH AIR.PROVIDE CPR/OXYGEN FOR UNCONSCIOUS PERSONS.FURTHER TREATMENT SHOULD BE SYMPTOMATIC AND SUPPORTIVE.
============ Fire Fighting Measures =============
Extinguishing Media:NON-FLAMMABLE GAS. USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
======== Accidental Release Measures =========
Spill Release Procedures:EVACUATE ALL PERSONNEL FROM AFFECTED AREA.USE APPROPRIATE PROTECTIVE EQUIPMENT.IF LEAK IS IN CONTAINER OR CONTAINER VALVE,CONTACT YOUR SUPPLIER. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions:STORE UPRIGHT,IN A COOL,DRY,WELL VENTILATED AREA BELOW 131F.USE ONLY IN WEL

L VENTILATED AREA.DO NOT DRAG, SLIDE OR ROLL CYLINDERS. Other Precautions: DO NOT ALLOW THE TEMPERATURE WHERE CYLINDERS ARE STORED TO EXCEED 130F(54C). USE A FIRST-IN FIRST-OUT INVENTORY SYSTEM. VALVE PROTECTION CAPS MUST REMAIN IN PLACE UNLESS CONTAINER IS SECURED WITH VALVE OUTLET PIPED TO USE POINT. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: POSITIVE PRESSURE AIR LINE WITH MASK OR SELF-CONTAINED BREATHING APPARATUS SHOULD BE A VAILABLE FOR EMERGENCY USE. Ventilation:LOCAL EXHAUST Protective Gloves: ANY MATERIAL Eye Protection: SAFETY GLASSES OR GOGGLES Other Protective Equipment: SAFETY SHOES Work Hygienic Practices: WASH HANDS. DO NOT SMOKE. Supplemental Safety and Health ========= Physical/Chemical Properties ============ HCC:G3 Boiling Pt:B.P. Text:-321F,-196C Melt/Freeze Pt:M.P/F.P Text:-346F,-210C Spec Gravity:0.97 Solubility in Water: VERY SLIGHTLY Appearance and Odor: COLORLESS, ODORLESS GAS Pe rcent Volatiles by Volume:100 ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES NONE

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES

Hazardous Decomposition Products: NONE

======= Disposal Considerations ===========

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF WASTE OR UNUSED QUANTITIES.RETURN IN THE SHIPPING CONTAINER PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE P

ROTECTION CAP IN PLACE TO YOUR SUPPLIER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.