

OCTAGON PROCESS INC. -- VV-C-846A TYPE 1 -- 9150-00-252-6380

=====
Product Identification
=====

Product ID:VV-C-846A TYPE 1
MSDS Date:09/24/1991
FSC:9150
NIIN:00-252-6380
MSDS Number: BLTXJ
=== Responsible Party ===
Company Name:OCTAGON PROCESS INC.
Address:596 RIVER ROAD
City:EDGEWATER
State:NJ
ZIP:07020-1105
Country:US
Info Phone Num:201-945-9400/FAX 201-945-1203
Emergency Phone Num:201-945-9400
0/FAX 72-1 -1203
CAGE:82925
=== Contractor Identification ===
Company Name:OCTAGON PROCESS INC.
Address:596 RIVER ROAD
Box:City:EDGEWATER
State:NJ
ZIP:07020
Country:US
Phone:201-945-9400
CAGE:82925

=====
Composition/Information on Ingredients
=====

Ingred Name:"NOT HAZARDOUS"
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5MG.M3 OIL MIST(MFR)
ACGIH TLV:5MG/M3 OIL MIST(MFR)

=====
Hazards Identification
=====

Routes of Entry: I

Inhalation: YES Skin: YES Ingestion: NO
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: ACUTE-EYES: MAY CAUSE IRRITATION &
REDNESS. SKIN: MAY CAUSE DRYING, IRRITATION & CONTACT
DERMATITIS. INHALATION: VAPORS MAY IRRITATE RESPIRATORY
TRACT. INGESTION: MAY CAUSE IRRITATION OF GI TRACT. MINUTE AMOUNTS
ASPIRATED INTO LUNGS MAY CAUSE MILD TO SEVERE PULMONARY INJURY &
POSSIBLY DEATH. CHRONIC- MAY CAUSE DERMATITIS.
Effects of Overexposure: MAY CAUSE EYE IRRITATION & REDNESS. MAY CAUSE
SKIN DRYING, IRRITATION & CONTACT DERMATITIS. INHALATION OF VAPORS
MAY IRRITATE RESPIRATORY TRACT. INGESTION MAY CAUSE IRRITATION OF
GI TRACT. MINUTE AMOUNTS ASPIRATED INTO LUNGS MAY CAUSE MILD TO
SEVERE PULMONARY INJURY & POSSIBLY DEATH.
Medical Condition Aggravated by Exposure: NO MEDICAL DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid: GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. INHALATION: REMOVE
TO FRESH
AIR. PROVIDE CPR IF NEEDED. EYE: FLUSH WITH WATER FOR AT
LEAST 15 MINUTES, HOLDING EYELIDS OPEN. SKIN: WASH WITH SOAP AND
WATER. INGESTION : DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL HELP.

=====
===== Fire Fighting Measures =====

Flash Point Method: COC
Flash Point: 380F, 193C
Extinguishing Media: CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard: NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures: DIKE & CONTAIN SPILL. RECOVER FREE LIQUIDS IF
POSSIBLE. ABSORB REMAINING PRODUCT WITH INERT MATERIAL & PLACE IN
PROPER CONTAINERS FOR DISPOSAL. DO NOT ALLOW MATERIAL TO ENTER
DRAINS, SEWERS OR WATERWAYS. COMPLY WITH HAZWOPER (29 CFR
1910.120).

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORAGE-STORE IN A COOL, DRY PLACE, AWAY FROM HEAT & FLAMES.

Other Precautions: EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE/EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE/WELD ON/OR NEAR CONTAINER. ALL LABEL WARNING AND PRECAUTIONS MUST BE OBSERVED UNTIL THE CONTAINER HAS BEEN THOROUGHLY CLEANED/DESTROYED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: NO SPECIAL REQUIREMENTS UNDER ORDINARY

CONDITIONS OF USE AND WITH ADEQUATE VENTILATION. IF EXCESSIVE MISTING (>5 MG/M³), USE SELF-CONTAINED BREATHING APPARATUS.

Ventilation: WHEN USE CONDITIONS ARE LIKELY TO RESULT IN EXCESSIVE MISTING (>5 MG/M³), PROVIDE ADEQUATE LOCAL VENTILATION.

Protective Gloves: PVC, NEOPRENE, BUTYL RUBBER, PVA, RUBBER

Eye Protection: SAFETY GLASSES - GOGGLES - FACE SHIELD

Other Protective Equipment: EYE WASH STATION & SAFETY SHOWER

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. LAUNDC

CONTAMINATED CLOTHING BEFORE REUSE. DISCARD OIL SOAKED SHOES.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE P/N A UNDER THE SAME NSN.

=====
===== Physical/Chemical Properties =====

HCC: V6

Boiling Pt: B.P. Text: 680F, 360C

Spec Gravity: 0.92

Evaporation Rate & Reference: