View NSN Online: https://aerobasegroup.de/nsn/6850-01-008-3781

GOULD INC RECORDING SYSTEMS DIV -- 23-5101-1 ELECTROSTATIC RECORDER TONER - 6850-01-008-3781

Product ID:23-5101-1 ELECTROSTATIC RECORDER TONER MSDS Date:08/01/1990 FSC:6850 NIIN:01-008-3781 MSDS Number: BLVBR === Responsible Party === Company Name: GOULD INC RECORDING SYSTEMS DIV Address:3631 PERKINS AVE City:CLEVELAND State:OH ZIP:44114-4632 Country:US Info Phon e Num:716-853-7500 Emergency Phone Num:716-853-7500 CAGE:MO498 === Contractor Identification === Company Name: GOULD INC RECORDING SYSTEMS DIV Address:3631 PERKINS AVE Box:City:CLEVELAND State:OH ZIP:44114-4632 Country:US Phone:716-853-7500 CAGE:MO498 Company Name: GOULD INC., TEST AND MEASUREMENT GROUP Address:8333 ROCKSIDE ROAD Box:City:VALLEY VIEW State:OH ZIP:44125-6104 Country:US Phone:216-328-7000 CAGE:96795

Ingred Name:C

ARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 0.4% Other REC Limits:3.5 MG/M3 OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:ISODODECANE (C10, C11 ISOPARAFFINIC HYDROCARBON) CAS:31807-55-3 Fraction by Wt: 2-3% Other REC Limits:200 PPM

Ingred Name:HYDROTREATED HEAVY NAPHTHA CAS:64742-48-9 Fraction by Wt: 96.5-97% Other REC Limits:300 PPM

Ingred Name:HEAVY AROMATIC NAPHTHA CAS:64742-94-5 Fraction by Wt: 0.6-1.0% Other REC Limits:100 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION: MAY CAUSE MUCOUS
MEMBRANE IRRITATION, AND CNS EFFECTS. EYE:IRRITATION.
SKIN:DEFATTING OF THE SKIN AND IRRITATION. INGESTION: MAY CAUSE
DIARRHEA, CNS DEPRESSION. SMALL AMOUNTS ASPIRA TED INTO LUNGS MAY
RESULT IN SEVERE PULMONARY INJURY OR DEATH. CHRONIC:DERMATITIS,
CHEMICAL PNEUMON
ITIS, KIDNEY DAMAGE.
Explanation of Carcinogenicity:THIS PRODUCT HAS NOT SHOWN ANY EVIDENCE
OF BEING CARCINOGENIC.
Effects of Overexposure:OVEREXPOSURE MAY LEAD TO RESPIRATORY
IRRITATION, NAUSEA, FATIGUE, DIZZINESS, HEADACHES, CENTRAL NERVOUS
SYSTEM EFFECTS, RESPIRATORY ARREST, OR UNCONSCIOUSNESS, DERMATITIS
AND EYE IRRITATION.

Medical Cond Aggravated by Exposure:SKIN, KIDNEY AND RESPIRATORY DISEASES.

Firs

t Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE :IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION:GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

FΙ

Spill Release Procedures: EVACUATE AREA. WEAR PROTECTIVE EQUIPMENT AND SCBA. SHUT OFF SOURCE, IF POSSIBLE CONTAIN SPILL. PROTECT FROM IGNITION. KEEP OUT OF WATER SOURCES AND SEWERS. ABSORB IN A DRY, INERT MATERIAL. TRANSFER TO DISPOSAL DRUMS USING NON-SPARKING EQUIPMENT.

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINERS CLOSED WHEN NOT

IN USE. EMPTY CONTAINERS MAY BE HAZARDOUS.

Other Precautions: AVOID CONTACT WITH EYES, SKIN, OR CLOTHING. AVOID BREATHING VAPORS. WEAR PROTECTIVE EQUIPMENT AND/OR GARMENTS. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. PROVIDE MEANS OF CONTROLLING LEAKS AND SPILLS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR. AIR-SUPPLIED OR FILTERING TYPE WITH ORG ANIC VAPOR CARTRIDGES ARE RECOMMENDED FOR CONCENTRATIONS EXCEEDING THE RECOMMENDED EXPOSURE LEVEL.
Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED. AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.
Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL
Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD
Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER.
Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.
WASH SKIN AFTER USING PRODUCT. DO NO
T EAT, DRINK OR SMOKE IN WORK AREA.
Supplemental Safety and Health

NONE

HCC:F4 Boiling Pt:=148.9C, 300.F B.P. Text:300F,149C Vapor Pres:1 Spec Gravity:0.75-0.80 Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK LIQUID, MILD ISOPARAFFINIC HYROCARBON ODOR. Percent Volatiles by Volume:>99

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING A GENTS Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND OTHER HYDROCARBON COMPOUNDS DURING COMBUSTION.

Waste Disposal Methods: WASTE MAY BE BURNED IN AN APPROVED INCINERATOR OR DISPOSED OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS.

Disclaimer (provided with this information

by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.