

DAVIS HOWLAND OIL CORP. -- VV-D-1078D 500 CS -- 9150-00-024-9621

=====  
Product Identification  
=====

Product ID:VV-D-1078D 500 CS

MSDS Date:04/17/1991

FSC:9150

NIIN:00-024-9621

MSDS Number: BLVZL

=== Responsible Party ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-473-6650

Emergency Phone Num:800-333-1622 X6650/716

-473-6650

CAGE:5A565

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SILICON FLUID/DIMETHYLPOLYSILOXANES

CAS:63148-62-9

Fraction by Wt: 80 - 99%

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS >40,000

MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE- EYE CONTACT: MAY CAUSE MILD

IRRITATION. SKIN/INHALATION/INGESTION: NONE KNOWN.

PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION. CHRONIC- NONE

KNOWN. MAY CAUSE SKIN IRRITATION AND DERMATITIS.

Effects of Overexposure:MILD EYE IRRITATION.

Medical Cond Aggravated by Exposure:NONE KNOWN.

=====  
S =====  
First Aid Measure

First Aid:INHALATION:MOVE TO FRESH AIR. SEEK MEDICAL ATTENTION IF NEEDED. EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. SEEK MEDICAL CARE IF SYMPTOMS PERSIST. SKIN: WASH WITH SOAP AND WATER. INGESTION:RINSE MOUTH WITH WATER SEVERAL TIMES. SEEK MEDICAL ASSISTANCE IF NECESSARY.

=====  
Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:575F,302C

Extinguishing Media:USE WATER FOG, C

ARBON DIOXIDE, FOAM, OR DRY

CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====  
Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER

FOR DISPOSAL. WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE SLIPPING HAZARD.

Neutralizing Agent:NOT APPLICABLE.

=====  
Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN A COOL PLACE AWAY FROM HEAT & FLAME.

Other Precautions:AVOID DIRECT OR PROLONGED CONTACT WITH EYES AND SKIN. WASH HANDS THOROUGHLY AFTER HANDLING. DO NOT EAT, DRINK, OR SMOKE IN WORK AREA.

=====  
Exposure Controls/Personal Protectio

n =====

Respiratory Protection:NONE NORMALLY REQUIRED. WEAR A NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR IF NECESSARY.

Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT.

Protective Gloves:NITRILE

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHIN G OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>400F,>204C

Vapor Pres:NEGLIGIBLE

Spec Gravity:0.97

Evaporation Rate & Reference: