

NONFLUID OIL CORP -- VV-G-632B -- 9150-00-273-2374

===== Product Identification =====

Product ID:VV-G-632B

MSDS Date:01/01/1989

FSC:9150

NIIN:00-273-2374

MSDS Number: BLWGF

=== Responsible Party ===

Company Name:NONFLUID OIL CORP

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Info Phone Num:201-344-3451

Emergency Phone Num:201-344-3451

CAGE:76736

=== Contractor Identificati

on ===

Company Name:NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

===== Composition/Information on Ingredients =====

Ingred Name:SEVERLY HYDROTREATED HEAVY NAPHTHENIC DISTILLATE

CAS:64742-52-5

RTECS #:PY8035000

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABL

E

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT TENDS TO REMOVE OILS AND MAY CAUSE SKIN IRRITATION. EXPOSURE TO FUMES OR MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:MAY CAUSE MILD IRRITATION OF SKIN AND MUCOUS

MEMBRANE.

=====
===== First Aid Measures =====

First Aid:SKIN CONTACT-WIPE OFF AND WASH WITH SOAP AND WATER. EYE CONTACT-FLUSH WITH COPIOUS AMOUNTS OF WATER AND SEE A DOCTOR. INHALE-REMOVE FROM EXPOSURE TO FRESH AIR. INGEST-ADMINISTER WATER AND SEEK MEDICAL AID. DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:390F,199C

Lower Limits:1%

Upper Limits:6%

Extinguishing Medi

a:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL (CAREFULLY TO PREVENT FROTHING).

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS WITH FACE SHIELD IN ENCLOSED AREAS.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. ELIMINATE IGNITION SOURCES. REMOVE FREE PRODUCT. ADD ABSORBENT MATERIAL SUCH AS CLAY TO SPILL AREA. SWEEP OR SCRAPE UP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. HANDLE AND STORE USING METHODS GENERALLY ADVOCATED FOR PETROLEUM PRODUCTS. DO NOT STORE OR MIX WITH OXIDIZING MATERIALS.

Other Precautions:AVOID EXCESSIVE HEAT OR FLAMES. AVOID REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH EYES AND INHALATION OF FUMES, VAPORS OR MIST. DO NOT INGEST. WAS THOROUGHLY AFTER HANDLING.

=====
===== Exposure

Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED. RECOMMENDED IF FUMING OR MISTING.

Ventilation:LOCAL EXHAUST AND MECHANICAL RECOMMENDED TO CAPTURE HOT FLAMES OR IF FUMING OR MISTING.

Protective Gloves:NEOPRENE RUBBER AS REQUIRED.

Eye Protection:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:NORMALLY NOT REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

DO NOT GET IN EYES OR ON CLOTHING.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:600F,316C

Vapor Pres:10

Spec Gravity:0.9

Evaporation Rate & Reference: