

OCTAGON PROCESS INC -- VV-P-236B -- 9150-01-023-3934

=====
Product Identification
=====

Product ID:VV-P-236B
MSDS Date:07/08/1988
FSC:9150
NIIN:01-023-3934
MSDS Number: BLXHV
=== Responsible Party ===
Company Name:OCTAGON PROCESS INC
Address:596 RIVER ROAD
City:EDGEWATER
State:NJ
ZIP:07020
Country:US
Info Phone Num:201-945-9400
Emergency Phone Num:201-945-9400
CAGE:82925
=== Contractor Identificat
ion ===
Company Name:OCTAGON PROCESS INC.
Address:596 RIVER ROAD
Box:City:EDGEWATER
State:NJ
ZIP:07020
Country:US
Phone:201-945-9400
CAGE:82925

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENTS

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acut

e and Chronic:HEATED MATERIAL MAY CAUSE BURNS TO SKIN.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:IF HEATED MATERIAL COMES IN CONTACT WITH SKIN, MAY CAUSE REDNESS & BLISTERING AS WITH A "HOT" OIL.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid:SKIN:FLUSH IMMEDIATELY W/PLENTY OF WATER. IF IRRITATION PERSISTS, GET MD. EYE:IMMEDIATELY FLUSH W/POTABLE WATER FOR A MINIMUM OF 15 MINS, SEEK ASSISTANCE FROM MD . INHAL:REMOVE TO FRESH AIR. SUP PORT BREATHING (GIVE O*2/ARTIFICIAL RESPIRATION) . INGEST:CALL MD IMMEDIATELY .

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:425F,218C

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE OR CHEMICAL FOAM.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. IF MATERIAL IS STILL SOLID, SCOOP UP & REUSE IF POSSIBLE. IF MATERIAL IS HEATED, ABSORB ON OIL-LOVING ABSORBENT & PLACE IN SUITABLE CONTAINERS FOR DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. KEEP AWAY FROM EXCESSIVE HEAT & OPEN FLAMES AS PRODUCT WILL MELT.

Other Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:RUBBER OR NEOPRENE GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:AS NEEDED TO AVOID SKIN CONTACT IF MATERIAL IS BEING USED HOT.

Work Hygienic Practices:WASH HANDS & FACE AFTER USING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety

and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:115F,46C
Spec Gravity:0.84 @ 60C
Solubility in Water:INSOLUBLE
Appearance and Odor:YELLOW TO AMBER COLORED SEMI-SOLID HYDROCARBON;
ODORLESS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazard
ous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &
FEDERAL ENVIRONMENTAL REGULATIONS. DO NOT ALLOW PRODUCT TO ENTER
WATERCOURSES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
express
ly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.