

TEXAS INSTRUMENTS INC SEMICONDUCTOR GROUP -- NICKEL CADMIUM BATEERY --  
6140-01-120-1097

===== Product Identification =====

Product ID:NICKEL CADMIUM BATEERY

MSDS Date:08/16/1991

FSC:6140

NIIN:01-120-1097

MSDS Number: BLZGW

=== Responsible Party ===

Company Name:TEXAS INSTRUMENTS INC SEMICONDUCTOR GROUP

Address:13500 N CENTRAL EXPY

Box:655303

City:DALLAS

State:TX

ZIP:75265-5303

Country:US

Info Phon

e Num:214-995-2011

Emergency Phone Num:214-995-2011

CAGE:01295

=== Contractor Identification ===

Company Name:TEXAS INSTRUMENTS

Address:MS 8308

Box:City:DALLAS

State:TX

ZIP:75265

Country:US

Phone:214-997-5417

CAGE:33809

Company Name:TEXAS INSTRUMENTS INC,SEMICONDUCTOR GROUP

Address:13500 N CENTRAL EXPY

Box:655303

City:DALLAS

State:TX

ZIP:75265-5303

Country:US

Phone:214-995-2011

CAGE:01295

===== Composition/Information on Ingredients =====

Ingred Name:NICKEL AND NICKEL HYDROXI

DE  
Fraction by Wt: 15%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:1.0 MG/M3  
ACGIH TLV:1.0 MG/M3

Ingred Name:CADMIUM AND CADMIUM HYDROXIDE  
Fraction by Wt: 28%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.1 MG/M3 (FUME)  
ACGIH TLV:0.05 MG/M3

Ingred Name:COBALT & COBALT HYDROXIDE  
Fraction by Wt: 0.6%  
Other REC Limits:NONE SPECIFIED

Ingred Name:POTASSIUM HYDROXIDE (SARA III)  
CAS:1310-58-3  
RTECS #:TT2100000  
Fraction by Wt: 2.5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:C, 2 MG/M3  
ACGIH TLV:C 2 MG/M3; 9  
192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:ELECTROLYTE IS CAUSTIC. CONTACT WITH  
SKIN OR EYES MAY CAUSE IRRITATION.  
Explanation of Carcinogenicity:NICKEL AND CADMIUM COMPOUND ARE LISTED  
AS CARCINOGENIC TO HUMANS BY IARC AND NTP.  
Effects of Overexposure:SKIN AND EYE CONTACT WITH POTASSIUM HYDROXIDE  
MAY CAUSE CHEMICAL BURNS.  
Medical Cond Aggravated by Exposure:AN ACUTE EXPOSURE WILL NOT  
GENERALLY AGGRAVATE ANY MEDICAL CONDITION.

=====  
===== First Aid Measures =====

First Aid:EYES OR SKIN: FLUSH WITH PLENTY OF RUNNING WATER FOR AT LEAST  
15 MINUTES AND CONTACT A PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Fire Fighting Procedures:UES SELF-CONTAINED BREATHING APPARATUS,  
PROTECTIVE

GLOVES AND EYE PROTECTION.

Unusual Fire/Explosion Hazard:CADMIUM FUMES MAY BE RELEASED DURING BURNING.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH ELECTROLYTE SPILLS WITH WATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT SHORT CIRCUIT; MAY CAUSE BURNS.

Other Precautions:AVOID INCINERATION OR MUTILATION.

===== Exposure Controls/Personal Protection =====

==

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE AND BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:=765.C, 1409.F

Melt/Freeze Pt:=321.1C, 610.F

Spec Gravity:8.6

Solubility in Water:0%

Appearance and Odor:CD IS A SILVER-WHITE MALLEABLE METAL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MA

NUFACTURER.

Stability Condition to Avoid:DO NOT DISASSEMBLE OR HEAT.

Hazardous Decomposition Products:DO NOT INCINERATE OR MUTILATE; MAY BURST OR RELEASE TOXIC MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United Sta

tes of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.