

CAAP CO INC -- CAAPCOAT POLYURETHANE THINNER -- 8010-00-459-1756

=====
Product Identification
=====

Product ID:CAAPCOAT POLYURETHANE THINNER

MSDS Date:11/01/1991

FSC:8010

NIIN:00-459-1756

Kit Part:Y

MSDS Number: BMCCS

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-877-0375

Emergency Phone Num:203-877-0375

Preparer's Name:CHRISTINE L. SLEDGE

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE (SARA 313)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 73.4%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM;150 PPM STEL

ACGIH TLV:100 PPM;150 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000

LBS

Ingred Name:METHYLISOBUTYLKETONE (SARA 313)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 26.6%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 845 GL, 7.05 LBS/GAL AS SUPPLIED.

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO I

ARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE EYES,
IRRITATE SKIN, CAUSE RESPIRATORY IRRITATION UPON INHALATION.

CHRONIC: REPEATED/PROLONGED EXPOSURE:

HEADACHES/NAUSEA/VOMITING/COMA. INHALATION OF VERY HIGH VAPOR
CONCENT RATIONS/PROLONGED EXPOSURE MAY CAUSE NEURAL DYSFUNCTION,
KIDNEY AND LIVER DAMAGE.

Effects of Overexposure:VAPOR: BURNING EYES/HEADACHE/DIZZINESS/THROAT
IRRITATION/LOSS OF APPETITE/NAUSEA/VOMITING. CONTACT: MAY CAUSE
IRRITAT

ION OF SKIN/BURNING OF SKIN/EYES.

Medical Cond Aggravated by Exposure:PREEXISTING ALLERGIES, EYE, SKIN
AND RESPIRATORY DISORDERS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LOTS OF RUNNING WATER FOR 15 MIN, LIFTING LIDS
OCCAS. IMMED MED ATTEN. SKIN: WASH W/SOAP/WATER. REMOVE
COMTAMINATED CLOTHING, WASH BEFORE REUSE. IF IRRITATION
PERSIST/SIGNS/SYMPTOMS OF E XPOSURE EXIST; IMMED MED ATTEN.
INHALE:MOVE TO FRESH AIR. ARTIFICIAL

RESPIRATION IF NOT BREATHING.

IMMED MED ATTEN. INGEST: IMMED MED ATTEN. DO NOT INDUCE VOMITING.
IF VOMITING OCCURS SPONTANEOUSLY*

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:68.0F,20.0C

Lower Limits:1

Upper Limits:8

Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM, CARBON DIOXIDE. DO NOT USE A DIRECT WATER STREAM.

Fire Fighting Procedures:FIRE FIGHTERS WEAR SCBA/FULL PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL CONTAINERS/STRUCTURES EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FLAM LIQUID. NO ACCUMULATION WATER PRODUCT MAY FLOAT AND REIGNITED ON SURFACE. NO IGNITION SOURCES-VAPOR HEAVIER THAN AIR, MAY TRAVEL-IGNITION SOURCE-FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:NO IGNITE SOURCES/SMOKING. PROTECT EQUIP/SOLVENT RESIST GLOVES/APRON/BOOTS/SCBA IN PRESSURE DEMAND MODE/POSITIVE PRESSURE AIR-SUPPLIED RSPRTR. CONTAIN SPILL W/ABSORB MATERIAL. CLEAN UP ABSORB/CONTAIN SECURELY. SWEEP/MOP AREA W/SOAP/WATER. VENT AREA.

===== Handling and Storage =====

Other Precautions:N/K *KEEP VICITM'S HEAD BELOW HIPS TO PREVENT BREATHING VOMITUS INTO LUNGS. ASPIRATION CAN CAUSE CHEMICAL PNEUMONTITS AND PULMONARY EDEMA/HEMORRAGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:VAPORS/MISTS GENERATED WEAR NIOSH APPROVED RESPIRATOR A

PPROPRIATE FOR THOSE EMISSION LEVELS AT POINT OF USE.

APPROPRIATE RESPIRATORS INCLUDE FULL FACEPIECE/PURIFYING CARTRIDGE
RESPIRATOR EQUIPPED FOR ORGANIC VAPORS AND MISTS, A SCBA IN **

Ventilation:PRODUCT NOT USED ALONE, USED IN CONJUNCTION W/CAAPCOAT
POLYURETHANE COATING. SPRAY BOOTH FOR SPRAY APPLICATIONS. ONLY***

Protective Gloves:SOLVENT RESISTANT GLOVES

Eye Protection:SOLVENT RESISTANT SAFETY GLASSES

Other Protective Equipment:SOLVENT RESISTANT APRON. NO CONTACT LENSES.

EYEW

ASH/SAFETY SHOWER NEARBY.

Work Hygienic Practices:WASH WELL WITH SOAP AND WATER AFTER HANDLING
THE PRODUCT.

Supplemental Safety and Health

KEY1:F3. KIT CONSISTS OF EIGHT PARTS. PART ONE HAS PNI I, PART TWO HAS
PNI J, PART THREE HAS PNI K ... THROUGH PNI P, SAME NSN. FORMULA
CHANGED.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:241FTO281F

Vapor Pres:8

Vapor Density:3.6

Spec Gravity:.85 (WATER=1)

pH:6

Viscosity: