BEACH CHEMICAL & PAPER CO INC -- SLYDE SILICONE SPRAY -- 9150-00-823-7860

Product ID:SLYDE SILICONE SPRAY MSDS Date:11/22/1988 FSC:9150 NIIN:00-823-7860 MSDS Number: BMCDH === Responsible Party === Company Name: BEACH CHEMICAL & PAPER CO INC Box:2575 City:VIRGINIA BEACH State:VA ZIP:23450 Country:US Info Phone Num:804-427-2002 Emergency Phone Num:804-427-2002 CAG E:HO845 === Contractor Identification === Company Name: BEACH CHEMICAL & PAPER CO. INC. Box:2575 City: VIRGINIA BEACH State:VA ZIP:23450 Phone:804-427-2002 CAGE:HO845 Company Name: BEACH CHEMICAL AND PAPER PRODUCTS Address:1704 SOUTHERN BLVD Box:City:VIRGINIA BEACH State:VA ZIP:23454-4528 Country:US Phone:804-498-2623 CAGE:2Z334

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Other REC Limits:NONE RECOMMENDED OSHA PEL:350 PPM ACGIH TLV:350 PPM/450STEL;9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 Other REC Limits:NONE SPECIFIED OSHA PEL:1000 PPM ACGIH TLV:SIMPLE ASPHYXIANT 91

Ingred Name:BUTANE CAS:106-97-8 RTECS #:EJ4200000 Other REC Limits:NONE SPECIFIED OSHA PEL:800 PPM ACGIH TLV:800 PPM; 9192

Ingred Name:NAPHTHA, MEDIUM ALIPHATIC/MINERAL SPIRITS CAS:64742-88-7 Other REC Limits:NONE SPECIF IED OSHA PEL:500 PPM (MFR) ACGIH TLV:100 PPM (MFR)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE & CHRONIC-MAY CAUSE TRANSIENT IRRITATION OF EYES. AT HIGH CONCENTRATIONS MAY CAUSE SIGNS OF ANESTHESIA & RESPIRATORY IRRITATION & DEFATTING THE SKIN. Effects of Overexposure:MAY CAUSE TRANSIENT IRRITATION OF EYES. AT HIGH

CONCENTRATIONS MAY CAUSE SIGNS OF ANESTHESIA & RESPIRATORY IRRITATION & DEFATTING THE SKIN. Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN: WASH WITH SOAP & WATER. EYE: FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED: REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED. ORAL: DO NOT INDUCE VOMITING. IF LARGE AMOUNTINGESTED, GET MEDI Flash Point:NONE FOR AEROSOL

Extinguishing Media:WATER SPRAY, CO2, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:INTENSIVE HEAT CREATED BY F

IRE OR SUN

LIGHT WILL CAUSE AEROSOLS TO BURST. DO NOT INCINERATE OR STORE ABOVE 120F. CONTAINS EXTREMELY FLAMMABLE PROPELLANT.

Spill Release Procedures: VENTILATE AREA. AVOID BREATHING VAPORS. CONTAIN LARGE SPILLS TO PREVENT WATER CONTAMINATION. RECOVER PRODUCT FOR USE. ABSORB RESIDUES ON ABSORBENT MATERIAL SUCH AS SAWDUST.

Handling and St

orage Precautions: STORAGE- STORE IN A COOL, DRY AREA.

KEEP LID ON. DO NOT LEAVE IN A HOT CAR OR AN AREA WARMER THAN 120F. Other Precautions:WASH THOROUGHLY AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN. DO NOT SPRAY TOWARD FACE. AVOID CONTACT WITH EYES AND SKIN. DO NOT BREATHE VAPORS OR MISTS.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED.FOR ENCLOSED AREAS USE NIOSH-APPROVED ORGANIC VA POR

CARTRIDGE RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS. Ventilation:LOCAL EXHAUST IS USUALLY ADEQUATE.HOWEVER,MECHANICAL

VENTILATION SHOULD BE USED WHEN SPRAYING IN ENCLOSED AREAS. Protective Gloves:NONE REQUIRED. IMPERVIOUS OPTIONAL Eye Protection:CHEMICAL GOGGLES/FACE SHIELDS Other Protective Equipment:PROTECTIVE CLOTHINGS, EYE-WASH FACILITIES, SAFETY SHOWER.

Work Hygienic Practices: WASH THOROUGHLY BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

====

HCC:V2 Vapor Pres:70 Spec Gravity:1.3 Evaporation Rate & amp; Reference: