

DEFT INC -- CAT, MIL-C-85285B, 37038, TYPE II 04BK004CA -- 8010-01-293-0783

=====  
Product Identification  
=====

Product ID:CAT, MIL-C-85285B, 37038, TYPE II 04BK004CA

MSDS Date:07/31/1991

FSC:8010

NIIN:01-293-0783

Kit Part:Y

MSDS Number: BMDWZ

=== Responsible Party ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVENUE

City:IRVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-474-0400

Emergen

cy Phone Num:800-424-9300 CHEMTREC

Preparer's Name:NORM GAUL

CAGE:33458

=== Contractor Identification ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Phone:800 424-9300

CAGE:33458

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC ISOCYANATE (VAPOR PRESSURE 0 MM HG) HEXAMETHYLE

NE

DIISOCYANATE (HDI) CAS NO: 822-06-0, FREE MONOMER CONTENT\*

CAS:28182-81-2

Fraction by Wt: 65%

Other REC Limits:TLV OF 1 MG/M3 MOBAY

Ingred Name:\*LESS THAN 0.7% BASED ON RESIN SOLIDS AT TIME OF  
MANUFACTURE. AFTER 3-6 MONTHS STORAGE, THE FREE MONOMER CONTENT MAY  
\*\*

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

Ingred Name:\*\*RISE TO A MAXIMUM OF 1.6%. THE ACGIH HAS PROPOSED A TLV  
OF 0.005 PPM TWA IN THE NOTICE OF INTENDED CHANGES FOR \*\*\*

RTECS #:9999999ZZ

Other REC Limits:N

ONE SPECIFIED

Ingred Name:\*\*\*1987-88. MOBAY RECOMMENDS A CEILING LEVEL OF 0.02 PPM.

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

Ingred Name:METHYL ISOBUTYL KETONE (VAPOR PRESSURE 15 MM HG)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL 3-ETHOXYPROPIONATE (VAPOR PRESSURE .7 MM HG)

CAS:763-69-9

RTECS #:UF3325000

Fraction by Wt: 10%

Other R

EC Limits:NONE SPECIFIED

Ingred Name:VOC: 355 G/L

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: VAPORS IRRITATING TO EYES/NOSE/

THROAT. INHALATION MAY CAUSE HEADACHE/DIFFICULT

BREATHING/UNCONSCIOUSNESS. CHRONIC: REPEATED OVEREXPOSURE/SINGLE

LARGE DOSE CAN CAUSE I

SOCYANATE SENSITIZATION, W HICH CAN CAUSE  
REACTION TO A LATER EXPOSURE OF ISOCYANATE LEVELS WELL BELOW TLV  
VALUE OF ISOCYANATE.

Effects of Overexposure:INHALE: IRRITATE RSPRTRY TRACT/ACUTE NERV SYST  
DEPRESS-PROG STEPS:  
HEADACHE/DIZZY/STAGGER/CONFUSION/UNCONSCIOUS/COMA. SKIN/EYE  
CONTACT: IRRITATE/SWELL/RED/RASH. EYES: LIQUID/AREOSOLS/VAPORS  
IRRITATE/T EAR/RED/SWELL/STING SENSATION. SKIN ABSORPTION:  
PROLONG/REPEAT IRRITATE/DRY/DEFAT/CRACK. ACUTE: IRRITATE/CORROSIVE

Medi  
cal Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY  
DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS. ISOCYANATE  
SENSITIZATION.

=====  
First Aid Measures  
=====

First Aid:INHALE: REMOVE TO FRESH AIR. RESTORE BREATHING. ASTHMATIC  
TYPE SYMPTOMS MAY DEVELOP/MAY BE IMMEDIATE OR DELAYED SEVERAL HRS.  
MED AID. SKIN: REMOVE CONTAM CLOTHING. WASH AFFECTED AREAS W/  
SOAP/WATER. W ASH CONTAM CLOTHING BEFORE REUSE. EYES:FLUSH W/CLEAN

LUKEWARM WATER (LOW PRESSURE) 15 MIN, LIFT LIDS. MED AID. INGEST:  
DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS  
PERSON. MED AID.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC

Flash Point:60.0F,15.6C

Lower Limits:1.05

Extinguishing Media:FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL,  
WATER FOG.

Fire Fighting Procedures:FULL EQUIP W/SCBA/FULL GEAR--FIRE FIGHTERS.  
WTR--COOL CLSD CNTNRS-PREVENT PRESS BLD-UP/AUTO IGN  
ITE/EXPLOS.

HDI/OTHER VAPORS GENERATED BY COMBUST/THERMAL DECOMP.

Unusual Fire/Explosion Hazard:CNTNRS CLSD. NO HEAT/SPARKS/ELEC  
EQUIP/OPEN FLAME. CLSD CNTNRS EXPLODE--EXPOSED EXTREME HEAT. APPLIC  
TO HOT SURFACES- SPECIAL PRECAUS. OVEREXPOSURE TO DECOMP

=====  
Accidental Release Measures  
=====

Spill Release Procedures:CLEAR AREA. REMOVE SOURCES OF IGNITION  
(FLAME/SPARK SOURCES/HOT SURFACES). VENTILATE AREA. CONTAIN AND  
REMOVE WITH INERT ABSORBENT



===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid: CONTACT WITH MOISTURE, MATERIAL WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURE.

Hazardous Decomposition Products: BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, TRACES OF HCN AND HDI.

===== Disposal Considerations =====

Waste Disposal Methods: IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED WITH CARE DUE TO PRODUCT RESIDUE/FLAMMABLE VAPOR. DO NOT INCINERATE CLOSED CONTAINERS. EPA HAZARDOUS WASTE NUMBER/CODE: D001, F003, F005.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.