View NSN Online: https://aerobasegroup.com/nsn/5970-00-689-8832

POLYMER PLASTECS CORP. -- INSULATING COMPOUND PT B -- 5970-00-689-8832

Product ID: INSULATING COMPOUND PT B MSDS Date:07/05/1990 FSC:5970 NIIN:00-689-8832 Kit Part:Y MSDS Number: BMGXW === Responsible Party === Company Name: POLYMER PLASTECS CORP. Address:65 DAVIDS DR. City:HAUPPAUGE State:NY ZIP:11788 Country:US Info Phone Num:516-231-1300 **Emergency Phone Num:516** -231-1300 Preparer's Name: J. HERMELE CAGE:LO827 === Contractor Identification === Company Name: POLYMER PLASTECS CORP. Address:65 DAVIDS DR. City:HAUPPAUGE State:NY ZIP:11788 Country:US Phone:516-231-1300 CAGE:LO827 Company Name: POLYMER PLASTICS CORP Address:65 DAVIDS DRIVE Box:City:HAUPPAUGE State:NY ZIP:11788 Country:US Phone:516-231-1300, 800-255-3924 CAGE:0H381

Ingred Name:DITUTILTIN DILAURATE/ORGANOTIN COMPOUND CAS:77-58-

7 RTECS #:WH7000000 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED OSHA PEL:0.1 MG/M3 AS TIN ACGIH TLV:0.1 MG/M3 AS TIN

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS 1470 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: TIN AND ITS SALTS ARE POORLY ABSORBED FROM THE GASTROINTESTINAL TRACT. CAUSES SEVERE IRRITATION

O EYES AND SKIN. CHRONIC- NONE KNOWN.

Effects of Overexposure:CAUSES SEVERE IRRITATION TO EYES AND SKIN. Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:CALL A DOCTOR IF SYMPTOMS PERSIST.EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES,HOLDING EYELIDS OPEN.SKIN:WASH WITH SOAP & WATER.INHALED:REMOVE TO FRESH AIR.ORAL:IF CONSCIOUS,DRINK MILK OR EGG WHITE BEATEN IN WATER AND INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

Flash Point Method:TCC

Т

Flash Point:500F,260C

Extinguishing Media:WATER SPRAY, CO2, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:NONE KNOWN.

Spill Release Procedures: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT AND PICK UP WITH SHOVEL.

 Handling and Storage Precautions:STORAGE-STORE AT AMBIENT TEMPERATURE (122F).AVERAGE SHELF LIFE IS 12 MOUTHS IN CLOSED CONTAINER.
Other Precautions:DO NOT GET IN EYES OR SKIN. WASH THOROUGHLY AFTER HANDLING. USE WITH ADEQUATE V ENTILATION.

======= Exposure Controls/Personal Protection ==========

Vapor Density:>1 Percent Volatiles by Volume:0 Corrosion Rate:NONE

Stability Indicator/Materials to Avoid:YES NONE KNOWN. Stability Condition to Avoid:HIGH TEMPERATURES, FLAME Hazardous Decomposition Products:NONE KNOWN.

Waste Disposal Methods:PLACE IN CLOSED CONTAINERS. CAREFULLY INCINERATE OR USE SANITARY LAND FILL IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.