

BRO TECH CORP DBA PUROLITE CO -- PUROLITE A-310 ANION ION EXCHANGE RESIN-B --  
6130-01-060-3679

===== Product Identification =====

Product ID:PUROLITE A-310 ANION ION EXCHANGE RESIN-B

MSDS Date:01/01/1990

FSC:6130

NIIN:01-060-3679

MSDS Number: BMGYT

=== Responsible Party ===

Company Name:BRO TECH CORP DBA PUROLITE CO

Address:3620 G ST

City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

Info Phone Num:2

15-668-9090

Emergency Phone Num:215-668-9090

CAGE:0A5A0

=== Contractor Identification ===

Company Name:BRO TECH CORP DBA PUROLITE CO

Address:3620 G ST

City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

Phone:215-423-8234

CAGE:0A5A0

Company Name:VAPONICS INC

Address:20 RESERVOIR PARK DR

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:617-982-9900

CAGE:34203

===== Composition/Information on Ingredients =====

Ingred Name:"NOT HAZARDOUS"

Fraction by Wt: 100%

Other REC Limits:N

ONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-EYES:MAY CAUSE MECHANICAL  
IRRITATION. CHRONIC- NONE KNOWN.  
Effects of Overexposure:EYE IRRITATION.  
Medical Cond Aggravated by Exposure:EYE DISORDERS

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS  
PERSIST.EYE/SKIN:FLUSH WITH  
WATER FOR 15 MINUTES.HOLD EYELIDS OPEN.INHALED:REMOVE TO FRESH  
AIR.ORAL:FLUSH OUT MOUTH WITH WATER.SEEK MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:CO2, WATER FOG OR DRY CHEMICAL. WATER SPRAY MAY BE  
USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.  
Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND  
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS W  
ITH FULL  
FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.  
Unusual Fire/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:RESIN BEADS ON FLOOR MAY MECHANICALLY CAUSE  
FLOOR TO BE SLIPPERY. USE CARE TO AVOID FALLS. SWEEP UP AND  
TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL.  
Neutralizing Agent:NOT APPLICABLE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-  
KEEP DRUMS AND PLASTIC BAGS  
SEALED TO PREVENT DRYING OR MOISTURE LOSS.  
Other Precautions:STORE BELOW 49C (120F) AND ABOVE 0C (32F). DO NOT  
RAISE DUST. AVOID CONTACT WITH EYES AND SKIN. AVOID BREATHING DUST.  
WASH THOROUGHLY AFTER HANDLING MATERIAL.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF WORKPLACE EXPOSURE  
LIMIT IS EXCEEDED, A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR  
DUST RESPIRATOR IS ADVISE

D.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO GET RID OF TRI-METHYLAMINE ODOR.

Protective Gloves:NONE

Eye Protection:DUST-RESISTANT SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION, EMERGENCY SHOWER

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

COMPANY MAKES TWO KINDS OF ION EXCHANGE RESIN (CARTRIDGE). FOR OTHER KIND, SEE PIN A, SAME NSN.

=====

==== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.11

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER BEIGE SPHERICAL BEADS WITH AMINE ODOR WHEN NEW

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS AND CONCENTRATED NITRIC ACID

Stability Condition to Avoid:FLAMES AND TEMPERATURES ABOVE 428F.

Hazardous Decomposition Products:CO, CO2, STYRENE, -N (CH2OH), NH3, DIVINYLBENZENE

===== Disposal Considerations =====

Waste Disposal Methods:CAN BE DISPOSED AS ORDINARY TRASH.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.