

POLYMERIC SYSTEMS, INC. -- PSI-601 SILICONE SEALANT -- 8040-00-833-9563

=====
Product Identification
=====

Product ID:PSI-601 SILICONE SEALANT
MSDS Date:12/14/1990
FSC:8040
NIIN:00-833-9563
Kit Part:Y
MSDS Number: BMQGV
=== Responsible Party ===
Company Name:POLYMERIC SYSTEMS, INC.
Address:WHEATLAND & MASON STREETS
City:PHOENIXVILLE
State:PA
ZIP:19460
Country:US
Info Phone Num:215-935-1170
Emergency Phone Num:215-935-1170
Preparer's Name:ED CLUFF
CAGE:0KND3
=== Contractor Identification ===
Company Name:POLYMERIC SYSTEMS, INC.
Address:723 WHEATLAND STREET
Box:City:PHOENIXVILLE
State:PA
ZIP:19460
Country:US
Phone:610-935-1170
CAGE:0KND3

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLTRIACETOXYSILANE
CAS:4253-34-3
RTECS #:VV4500000
Fraction by Wt: 2-6%
Other REC Limits:NONE SPECIFIED

Ingred Name:ETHYLTRIACETOXYSILANE
CAS:17689-77-9
Fraction by Wt

: 2-6%
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 0.4 LBS/GAL; 40 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SEVERE IRRITATION TO
RESPIRATORY TRACT, PULMONARY EDEMA, EYE LACRIMATION, CORNEAL EDEMA;
SKIN IRRITATION AND DERMATITIS. CHRONIC: BRONCHI
TIS, LARYNGITIS;
DERMATITIS; CONJUNCTIVITIS.
Explanation of Carcinogenicity:NOT CARCINOGENIC
Effects of Overexposure:IRRITATION TO SKIN, EYES AND MUCOUS MEMBRANES.
MAY CAUSE DISCOMFORT, TEARING, CHOKING OR BURNING SENSATION.
Medical Cond Aggravated by Exposure:RESPIRATORY, SKIN OR EYE DISEASES.

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR. WASH SKIN WITH SOAP AND WATER. FLUSH
EYES WITH WATER FOR AT LEAST 15 MINUTES.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:>400F,>204C
Extinguishing Media:WATER SPRAY, CO2, DRY CHEMICALS, FOAM, SAND
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS
OPERATED IN POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:TOXIC GASES AND AEROSOLS MAY BE PRODUCED
BY COMBUSTION (CO AND SIO2).

===== Accidental Release Measures =====

Spill Release Procedures:MATERIAL RELEASES ACETIC ACI

D ON EXPOSURE TO

AIR. PROVIDE ADEQUATE VENTILATION DURING CLEAN UP. WEAR PROPER PROTECT EQUIPMENT IF HANDLING LARGE AMOUNTS. TRANSFER TO WASTE CONTAINER. LET CURE TO SOLID RUBBER, LET ALL LIBERATED ACETIC ACID DISSIPATE.

Neutralizing Agent:AQUEOUS SODIUM BICARBONATE

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED SKIN CONTACT. LIBERATED ACETIC ACID VAPORS CAUSE IRRITATION TO SKIN, EYES AND BRONCHIAL T ISSUES. DO NOT INGEST.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CLOSED SPACE WITH INADEQUATE VENTILATION USE CHEMICAL CARTRIDGE RESPIRATOR WITH FULL FACE PIECE & ORGANIC VAPOR CARTRIDGE (NIOSH/MSHA APPROVED) TO PROTECT AGAINST ACETIC ACID VAPORS.
Ventilation:RECOMMENDED 10 AIR CHANGES PER HOUR
Protective Gloves:DISPOSABLE PLASTIC
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE
Work Hygienic Practices:WASH BEFORE EATING, DRINKING OR SMOKING. DO NOT RUB EYES WHILE WORKING WITH SEALANT.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Decomp Temp:Decomp Text:>752F,>400C
Vapor Pres:< 5 MM
Vapor Density:2.07
Spec Gravity:1.04
pH:3-5
Viscosity:10-20000POISE
Solubility in Water:MODERATE
Appearance and Odor:THICK PASTE, VINEGAR LIKE ODOR
Percent Volatiles by Volume:4-7

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

AVOID PROLONGED CONTACT WITH MOISTURE DURING STORAGE.

Hazardous Decomposition Products: ACETIC ACID FROM MOISTURE CONTACT. CO
AND VOLATILE ORGANICS AND SILICA AEROSOLS FROM THERMAL DEGRADATION.

===== Disposal Considerations =====

Waste Disposal Methods: NOT AN EPA HAZARDOUS WASTE. DISPOSE OF IN
ACCORDANCE WITH APPROPRIATE GOVERNMENTAL REGULATIONS.

Disclaimer (provided with this information by the compi
ling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.