View NSN Online: https://aerobasegroup.de/nsn/9150-00-186-6699

MOBIL OIL CORP -- MOBIL DELVAC 1200 SUPER 15W-40 -- 9150-00-186-6699

Product ID:MOBIL DELVAC 1200 SUPER 15W-40 MSDS Date:12/03/1991 FSC:9150 NIIN:00-186-6699 MSDS Number: BMQRV === Responsible Party === Company Name: MOBIL OIL CORP Address:3225 GALLONS ROAD City:FAIRFAX State:VA ZIP:22037-0001 Country:US Info Phone Num:800-424-9300 Emergency Phone Num:703-849-3265 OR 212-883-4411 CAGE:1E969 === Contractor Identification === Company Name: MOBIL OIL CORP Address:530 EAST SWEDESFORD ROAD Box:1031 **City:VALLEY FORGE** State:PA ZIP:19482 Country:US Phone:703-849-3265 CAGE:1E969 Company Name: MOBIL OIL CORPORATION **City:PENNINGTON** State:NJ ZIP:08534 Country:US Phone:212-883-4411 CAGE:78253

Ingred Name:SEVERELY SOLVENT REFINED AND SEVERELY HYDROTREATED MINERAL BASE OILS. Fraction by Wt: >90.0% Other REC Limits:5 MG/M3 OIL MIST

Ingred Name: POLYOLEFIN AMIDE ALKENEAMINE Other REC Limits: NONE SPECIFIED

Ingred Name:BORONATED SUBSTITUTED SUCCINIMIDE Other REC Limits:NONE SPECIFIED

Ingred Name:CALCIUM SULFONATE OVERBASED Other REC Limits:NONE SPECIFIED

Ingred Name:OLEFIN POLYMERS Other REC Limits:NONE SPECIFIED

Ingred Name:BUTENE, HOMOPOLYMER CAS:9003-29-6 Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation: NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-INGESTION:NAUSEA, VOMITING., MINUTE AMOUNTS ASPIRATED INTO LUNGS MAY CAUSE PULMONARY INJURY AND EVEN DEATH. INHALATION OF MIST MAY CAUSE CHEMICAL PNEUMONITIS. EYE:IRRITATION. SKIN: IRRITATION, D EFATTING. CHRONIC-SKIN:IRRITATION, DERMATITIS. Effects of Overexposure:EYE-IRRITATION. SKIN-DRYNESS, IRRITATION. Medical Cond Aggravated by Exposure:INDIVIDUALS WITH EXIST ING SKIN DISEASES MAY BE AT INCREASED RISK.

First Aid:EYE-FLUSH WITH WATER FOR 15 MINUTES BY HOLDING EYELID OPEN. IF IRRITATION OR REDNESS PERSIST CONSULT A PHYSICIAN. SKIN-REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. INGESTION: DO NOT INDU CE VOMITING. CONSULT PHYSICIAN IMMEDIATELY. INHALATION OF OIL MIST OR FUMES, REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. GET MEDICAL HELP.

===

Flash Point Method:COC
Flash Point:>390F,>199C
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS.
Fire Fighting Procedures:DO NOT USE WATER STREAM DIRECTLY. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL.
Unusual Fire/Explosion Hazard:DO NOT HANDLE OR STORE NEAR HEAT OR FLAMES. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Spill Release Procedures :RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. DIKE AND KEEP PRODUCT OUT OF SEWERS & WATER COURSES. PUT WASTE IN A CONTAINER FOR PROPER DISPOSAL. Neutralizing Agent:NONE

Handling and Storage Precautions: MINIMIZE SKIN CONTACT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STORE NEAR EXTREME HEAT OR OPEN FLAMES.

Other Precautions:DO NOT CREATE MIST. DO NOT INHALE MIST OR VA PORS

PRODUCED AT HIGH TEMPERATURES. IF WORKING WITH MIST OR FUMES, NIOSH APPROVED SELF BREATHING RESPIRATOR WITH ORGANIC VAPORS FILTER MUST BE WORN. WASH TH OROUGHLY AFTER HANDLING.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. IF WORKING WITH MIST OR FUMES, USE NIOSH APPROVED SELF BREATHING RESPIRATOR WITH ORGANIC VAPOR FILTER. Ventilation:NORMAL OR MECHANICAL Protective Gloves:CHEMIC AL RESISTANT Eye Protection:SPLASH GOGGLES

Other Protective Equipment: CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING.

Work Hygienic Practices: WASH HANDS AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORKING AREA.

Supplemental Safety and Health

HCC:V6 Boiling Pt:B.P. Text:>600F,>316C Vapor Pres: