

AUFHAUSER BROTHERS CORP -- AUFHAUSER 4043 -- 3439-00-247-2982

=====  
Product Identification  
=====

Product ID:AUFHAUSER 4043

MSDS Date:08/29/1988

FSC:3439

NIIN:00-247-2982

MSDS Number: BMSVV

=== Responsible Party ===

Company Name:AUFHAUSER BROTHERS CORP

Address:39 WEST MALL

City:PLAINVIEW

State:NY

ZIP:11803-4209

Country:US

Info Phone Num:516-694-8696

Emergency Phone Num:516-694-8696

CAGE:59401

=== C

Contractor Identification ===

Company Name:AUFHAUSER CORP

Address:39 WEST MALL

Box:City:PLAINVIEW

State:NY

ZIP:11803-4209

Country:US

Phone:212-757-6824/FAX: 516-694-8690

CAGE:59401

=====  
Composition/Information on Ingredients  
=====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Fraction by Wt: 1.0%

Other REC Limits:NONE SPECIFIED

Ingred Name:CHROMIUM (SARA III) \*

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 0.1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1 MG/M3 \*

ACGIH TL

V:0.5 MG/M3; 9192 \*

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ZINC (SARA III) \*

CAS:7440-66-6

RTECS #:ZG8600000

Fraction by Wt: 0.5%

Other REC Limits:5 MG/M3 OXIDE

OSHA PEL:10 MG ZNO/M3 \*

ACGIH TLV:10 MG ZNO/M3; 9192 \*

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:MANGANESE (SARA III) \*

CAS:7439-96-5

RTECS #:OO9275000

Fraction by Wt: 1.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 DUST \*

ACGIH TLV:5 MG/M3 DUST 9192 \*

Ingred Name:COPPER (SARA III) \*

CAS:7440-50-8

RTECS #:GL53

25000

Fraction by Wt: 0.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.1MG/M3 FUME/1 DUST

ACGIH TLV:0.2MG/M3 FUME; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SILICON \*

CAS:7440-21-3

RTECS #:VW0400000

Fraction by Wt: 6.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3 TDUST \*

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TITANIUM, METAL

CAS:7440-32-6

RTECS #:XR1700000

Fraction by Wt: 0.5%

Other REC Limits:NONE SPECIFIED

Ingred Name:ALUMINUM (SARA III) \*

CAS:7429-90-5

RTECS #:BD0

330000  
Fraction by Wt: >85%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15MG/M3 DUST/5 FUME  
ACGIH TLV:10MG/M3 DUST; 9192 \*

Ingred Name:MAGNESIUM  
CAS:7439-95-4  
RTECS #:OM2100000  
Fraction by Wt: 6.0%  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:SHORT TERM EXPOSURE TO WELDING FUMES,  
GASES OR DUS  
T MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA,  
FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES. SKIN  
SENSITIVITY MAY ALSO BE NOTED. L ONG TERM EXPOSURE TO  
FUMES/GASES/DUST MAY CAUSE PULMONARY IRRITATION OR PNEUMOCONIOSIS;  
& SIDEROSIS FROM IRON FUMES.  
Explanation of Carcinogenicity:CHROMIUM & ALUMINUM ARE LISTED AS  
CARCINOGENIC. RESPIRATORY CANCER FROM WELDING IS UNCONFIRMED.  
Effects of Overexposure:EXPOSURE TO WELDING FUMES MAY RESULT IN  
DISCOMFORT SUCH A  
S DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR  
IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE  
NOTED. WATERY EYES, HEADACHE, BREA THING DIFFICULTY, FREQUENT  
COUGHING AND/OR CHEST PAINS MAY OCCUR FROM ACUTE EXPOSURE. TOXIC  
GASES CAN BE FATAL.  
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH IMPAIRED PULMONARY  
FUNCTION OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY IRRITANTS  
CONTAINED IN WELDING FUMES.

===== First Aid Measures =====  
=====

First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL  
FROM EXPOSURE AREA AND ADMINISTRATION OF FIRST AID. REMOVE FROM  
EXPOSURE AREA AND CALL FOR MEDICAL AID. ADMINISTER OXYGEN IF  
BREATHING IS D IFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL  
RESPIRATION. IF NO DETECTABLE PULSE, BEGIN EXTERNAL HEART MASSAGE.  
EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS.

===== Fire Fighting Measures =====

Extin

quishing Media:NON-FLAMMABLE

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSURE.

===== Handling and Storage =====

Handling and Storage Precautions:WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS.

Ventilation:USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR WELDING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE

Protective Gloves:FLAMEPROOF GAUNTLET GLOVES

Eye Protection:OSHA APPROVED GOGGLES/FACE SHIELD W/LENS

Other Protective Equipment:FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safe

ty and Health

WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THE PRESENCE OF CONTAMINANTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES.

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:1600F,871C

Spec Gravity:8.4

Solubility in Water:

NEGLIGIBLE

Appearance and Odor:SILVER OR YELLOW TO RED IN COLOR, SOLID ROD, NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS & ALKALIES.

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:WELDING/CUTTING OPERATIONS MAY INCLUDE ELEMENTAL METALS, OXIDES OF THE METALS, FUMES/GASES & ELECTROMAGNETIC RADIATION.

===== Disposal Considerations =====

Waste Di

posal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.