View NSN Online: https://aerobasegroup.de/nsn/6850-01-343-2257

RICOH CORPORATION -- SP-35 TONER, SAVIN TONER TYPE L1, 9350 TONE -- 6850-01-343-2257

Product ID:SP-35 TONER, SAVIN TONER TYPE L1, 9350 TONE MSDS Date:10/19/1990 FSC:6850 NIIN:01-343-2257 **MSDS Number: BMTBF** === Responsible Party === Company Name: RICOH CORPORATION Address:5 DEDRICK PLACE City:WEST CALDWELL State:NJ ZIP:07006 Country:US Info Phone Num:201-882-2000 E mergency Phone Num:800-336-6737 Preparer's Name: KRISTINA SAGE CAGE:54726 === Contractor Identification === Company Name: RICOH CORPORATION Address:5 DEDRICK PLACE City:WEST CALDWELL State:NJ ZIP:07006-6304 Country:US Phone:800-336-6737 CAGE:54726 **Company Name:SAVIN CORPORATION** Address:30 W GUDE DRIVE SUITE 350 Box:12070 City:ROCKVILLE State:MD ZIP:20850-4015 Country:US Phone:301-517-4272 FAX 301-517-4269 CAGE:4M009

Ingred Nam

e:HYDROTREATED HEAVY NAPHTHA CAS:64742-48-9 Fraction by Wt: 78% Other REC Limits:NONE SPECIFIED

Ingred Name:ACRYLIC POLYMER CAS:25068-63-7 Fraction by Wt: 8% Other REC Limits:NONE SPECIFIED

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 5% Other REC Limits:NONE SPECIFIED OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:WAX CAS:8002-74-2 RTECS #:RV0350000 Fraction by Wt: 10% Other REC Limits:NONE SPECIFIED

Ingred Name:WAX CAS:8015-86-9 Fraction by Wt: 3% Othe r REC Limits:NONE SPECIFIED

LD50 LC50 Mixture:ORAL RAT LD50 IS >12400 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:PRODUCT IS PRACTICALLY NON-TOXIC. IT PRODUCES PHYSICAL IRRITATION OF BODY TISSUES. NO CHRONIC EFFECTS ARE KNOWN. Explanation of Carcinogenicity:MFR SHOWS THAT CARBON BLACK IS LISTED BY IARC AS I

NADEQUATE EVIDENCE. Effects of Overexposure:HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO EYES AND RESPIRATORY TRACT. MAY CAUSE HEADACHE, DIZZINESS, OR HAVE OTHER CEENTRAL NERVOUS SYSTEM EFFECTS. Medical Cond Aggravated by Exposure:NO INFORMATION GIVEN ON MSDS BY SUPPLIER
======================================
 First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:D O NOT INDUCE VOMITING. GIVE 2 LARGE GLASSES OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE,SEE A DOCTOR.
======================================
Flash Point Method:TCC Flash Point:142F,61C Lower Limits:0.7 Upper Limits:6.5 Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fi re Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDENTS.
======================================
Spill Release Procedures: ELIMINATE IGNITION SOURCES AND VENTILATE AREA. RECOVER FREE PRODUCT AND ABSORB REMAINDER. KEEP OUT OF SEWERS AND WATERCOURSES BY DIKING. Neutralizing Age nt:NONE
======================================
 Handling and Storage Precautions:*COMBUSTIBLE LIQUID!* STORE IN A COOL, DRY, DARK AREA. KEEP AWAY FROM IGNITION SOURCES. KEEP OUT OF REACH OF CHILDREN Other Precautions:'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR. TREAT THEM WITH THE RESPECT DUE FULL ONES. DO NOT CUT,WELD,ETC. ON THEM.
======================================

Respiratory Protection:RESPIRATOR WILL NOT N

ORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED RESPIRATOR FOR DUST IF EXPOSURE IS ABOVE THE TLV/PEL FOR NUISANCE DUST. Ventilation:NOT NORMALLY REQUIRED. Protective Gloves:NONE Eye Protection:NONE Other Protective Equipment:NONE REQUIRED Work Hygienic Practices:USE OF GOOD PERSONAL HYGIENE PRACTICES, MINIMIZE ANY CONTACT. WASH AFTER USING AND BEFORE EATING, DRINKING OR SMOKING. Supplemental Safety and Health FOR USE WITH COPIER/SORTER NSN 3610-01-195-4587.

HCC:N1 Boiling Pt:B.P. Text:349F,176C Vapor Pres:5 MM Vapor Density:>5.9 Spec Gravity:0.8 Evaporation Rate & amp; Reference:0.04 (N-BUTYL ACETATE = 1 Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK LIQUID, NO ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:NO INFORMATION GIVEN ON MSDS BY SUPPLIER Hazardous Decompositi on Products:CARBON MONOXIDE AND OTHER PRODUCTS OF INCOMPLETE COMBUSTION.

Waste Disposal Methods:DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL REGULATIONS. MANUFACTURER MAKES NO SUGGESTIONS AS TO METHOD OF DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatso

ever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.