

INLAND PACKAGING -- INNERBOND 2010 FLUID 100 CST -- 9150-00-269-8246

=====  
Product Identification  
=====

Product ID:INNERBOND 2010 FLUID 100 CST

MSDS Date:04/23/1990

FSC:9150

NIIN:00-269-8246

MSDS Number: BMTXB

=== Responsible Party ===

Company Name:INLAND PACKAGING

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Info Phone Num:502-737-6757

Emergency Phone Num:502-737-6758

CAGE:66172

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POLYDIMETHYL SILOXANE

CAS:9016-00-6

RTECS #:TQ2690000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:LD50> 5000MG/KG

Routes of Entry: Inh

alation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: MAY CAUSE SOME IRRITATION TO EYES. CHRONIC: NONE SPECIFIED BY MANUFACTURER.  
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR A SUSPECTED CARCINOGEN.  
Effects of Overexposure:EYES: REDNESS, TEARING, ITCHING.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
st Aid Measures =====

First Aid:INHALATION: REMOVE PERSON FROM EXPOSURE. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. INGESTION: INDUCE VOMITING. SEE DOCTOR IF SYMPTOMS DEVELOP.

=====  
Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:570F,299C  
Extinguishing Media:WATER FOG, FOAM, CARBON DIOXIDE, OR DRY CHEMICAL  
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARAT  
US AND  
PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures =====

Spill Release Procedures:USE ABSORBANT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.

=====  
Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA IN TIGHTLY CLOSED CONTAINERS. STORE AWAT FROM HEAT (GREATER THAN 570F) AND MOISTURE.  
Other Precautions:DO NOT EAT, DRINK, OR SMOKE IN WORK AREA.

=====  
Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.  
Ventilation:GENERAL MECHANICAL VENTILATION.  
Protective Gloves:WORK GLOVES  
Eye Protection:SAFETY GLASSES.  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.  
Supplemental

Safety and Health

AVOID BREATHING VAPORS. AVOID DIRECT OR PROLONGED CONTACT WITH SKIN OR EYES.

===== Physical/Chemical Properties =====

HCC:V6

Melt/Freeze Pt:M.P/F.P Text:-65F,-54C

Vapor Pres:0.01 @392F

Spec Gravity:0.977/25C

Viscosity:100 CST

Solubility in Water:NEGLIGBLE

Appearance and Odor:CLEAR, COLORLESS PASTE-LIKE POLYMER

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG MINERAL ACIDS AN

D STRONG ALKALIS

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:OXIDES OF CARBON AND SILICON AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods:CALL LOCAL ENVIRONMENTAL OFFICER. DISPOSE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is form

ulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.