

ALLEN-BRADLEY CO -- 150 CENTISTOKES SILICONE DASH POT FLUID -- 9150-01-091-9706

=====
Product Identification
=====

Product ID:150 CENTISTOKES SILICONE DASH POT FLUID

MSDS Date:02/16/1994

FSC:9150

NIIN:01-091-9706

MSDS Number: BMWLC

=== Responsible Party ===

Company Name:ALLEN-BRADLEY CO

Address:1201 S 2ND ST

Box:2086

City:MILWAUKEE

State:WI

ZIP:53204

Country:US

Info Phone Num:414-382-2000

Emergenc

y Phone Num:414-382-2000

CAGE:01121

=== Contractor Identification ===

Company Name:ALLEN-BRADLEY CO

Address:1201 S 2ND ST

Box:2086

City:MILWAUKEE

State:WI

ZIP:53204

Country:US

Phone:414-382-2000

CAGE:01121

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYDIMETHYL SILOXANE

CAS:9016-00-6

RTECS #:TQ2690000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Sk

in:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-THERE IS NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION FOR ANY ROUTE OF EXPOSURE. CHRONIC-NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION.

Explanation of Carcinogenicity:MANUFACTURER GAVE NO INFORMATION ABOUT CARCINOGENICITY. HMIS DOES NOT EXPECT IT TO BE CARCINOGENIC.

Effects of Overexposure:NONE CURRENTLY KNOWN.

Medical Cond Aggravated by Exposure:A K

KNOWLEDGE OF THE AVAILABLE

TOXICOLOGY INFORMATION, PHYSICAL & CHEMICAL PROPERTIES OF THE MATERIAL SUGGESTS THAT OVEREXPOSURE IS UNLIKELY TO AGGRAVATE EXISTING MEDICAL CONDITIONS.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER. SKIN:WASH W/SOAP & WATER. SWALLOWING:NO HARMFUL EFFECTS EXPECTED. **NOTE TO PHYSICIAN** THERE IS NO SPECIFIC ANTIDOTE. TREATMENT OF OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS & THE CLINICAL CONDITION OF THE PATIENT.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>300F,>149C

Lower Limits:NOT DETERMIN

Upper Limits:NOT DETERMIN

Extinguishing Media:ALCOHOL/UNIVERSAL TYPE FOAMS APPLIED BY MFR'S RECOMMENDED TECHNIQUES FOR LARGE FIRES; CO2, DRY CHEMICAL FOR SMALL FIRES.

Fire Fighting Procedures:DO NOT SPRAY SOLID STREAM OF WATER OR FOAM INTO HOT BURNING LIQUIDS AS THIS MAY CAUSE FROTHING & INTENSIFY FIRE

. USE SCBA TO FIGHT FIRES IN ENCLOSED AREAS.

Unusual Fire/Explosion Hazard:IN EXTREME FIRE CONDITIONS, THIS MATERIAL MAY PRESENT A FLOATING FIRE HAZARD.

=====
===== Accidental Release Measures =====

Spill Release Procedures:COLLECT FOR DISPOSAL.

Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUTIONS COMMON TO GOOD MANUFACTURING PRACTICE SHOULD BE

FOLLOWED IN HANDLING & STORAGE.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED IN NORMAL USE.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS EXPECTED TO BE SATISFACTORY.

Protective Gloves:PVC COATED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION AND EMERGENCY SHOWERS.

Work Hygienic Practices:MFR:? HMIS:USE GOOD INDUSTRIAL HYGIENE PRACTICES. MINIMIZE CONTACT & WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:>392F,>200C

Melt/Freeze Pt:M.P/F.P Text: