

EASTMAN KODAK COMPANY -- 142 4654 FLEXICOLOR BLEACH III, PROCESS C-41, PART B --  
6750-01-022-8410

===== Product Identification =====

Product ID:142 4654 FLEXICOLOR BLEACH III, PROCESS C-41, PART B

MSDS Date:11/22/1996

FSC:6750

NIIN:01-022-8410

MSDS Number: BMWXD

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info P

hone Num:716-477-3194/MSDS 800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Infor

mation on Ingredients =====

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 75-80%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM FERRIC PROPYLENEDIAMINETETRAACETIC ACID  
CAS:111687-36-6  
Fraction by Wt: 10-15%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM NITRATE (SOLUTION) (SARA III)  
CAS:6484-52-2  
RTECS #:BR9050000  
Fraction by Wt: 7%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (SARA III)  
CAS:64-19-7  
RTECS #:AF1225000  
Fraction by Wt: 1  
-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 PPM  
ACGIH TLV:10 PPM/15 STEL; 9394  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM ACETATE (SARA III)  
CAS:631-61-8  
RTECS #:AF3675000  
Fraction by Wt: 212F,>100C  
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN  
Vapor Pres:18  
Vapor Density:0.6  
Spec Gravity:1.09  
pH:3.3  
Evaporation Rate & Reference:NOT GIVEN  
Solubility in Water:COMPLETE  
Appearance and Odor:GREEN LIQUID, VINEGAR ODOR  
Percent Volatiles by Volume:75-80%

===== Stabi

lity and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS,  
COMBUSTIBLE MATERIAL, STRONG REDUCING AGENTS.

Stability Condition to Avoid: MATERIAL CAN DECOMPOSE ABOVE 419F. AVOID  
TEMPERATURES ABOVE 239F.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE,  
HYDROGEN BROMIDE, AMMONIA, CHLORAMINE, NITROGEN OXIDES

===== Disposal Considerations =====

Waste

Disposal Methods: DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT  
TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH  
< 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE  
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this info

rmation to be accurate and

disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.