

SHERWIN WILLIAMS CO. -- F65E27 -- 8010-01-060-6457

=====  
Product Identification  
=====

Product ID:F65E27

MSDS Date:08/01/1991

FSC:8010

NIIN:01-060-6457

MSDS Number: BMWXX

=== Responsible Party ===

Company Name:SHERWIN WILLIAMS CO.

Address:101 PROSPECT AVE N.W.

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Info Phone Num:216-566-2902

Emergency Phone Num:216-566-2917

CAGE:88573

=== Contractor Identific

ation ===

Company Name:THE SHERWIN WILLIAMS CO. DIVERSIFIED BRANDS

Address:101 PROSPECT AVE N.W.

Box:City:CLEVELAND

State:OH

ZIP:44115

Country:US

Phone:(800)-832-2541/ EMER: 216-566-2917

CAGE:88573

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HYDROTREATED LIGHT PETROLEUM DISTILLATE

CAS:64742-47-8

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:NAPHTHA, MEDIUM ALIPHATIC

CAS:64742-88-7

Other REC Limits:NONE SPECIFIED

Ingred Nam

e:DIPROPYLENE GLYCOL METHYL ETHER  
CAS:34590-94-8  
RTECS #:JM1575000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:S,100PPM/150STEL  
ACGIH TLV:S,100PPM/150STEL9192

Ingred Name:TALC (CONTAINING ASBESTOS)  
CAS:14807-96-6  
RTECS #:MW2700000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.2 FIBERS/CC  
ACGIH TLV:0.2 FIBERS/CC; 9192

Ingred Name:CALCIUM CARBONATE  
CAS:471-34-1  
RTECS #:FF9335000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:10 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR  
2275000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:POTASSIUM ZINC CHROMATE  
CAS:11103-86-9  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:UNK  
ACGIH TLV:0.05

Ingred Name:LEAD SULFOCHROME  
CAS:1344-37-2  
Other REC Limits:NONE SPECIFIED

Ingred Name:LEAD CHROMATE MOLYBDATE  
CAS:12656-85-8  
RTECS #:QA4660000  
Other REC Limits:NONE SPECIFIED

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES I

ngestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:IRRITATION OF EYES,SKIN AND  
RESPIRATORY SYSTEM,MAY CAUSE CNS DEPRESSION.

Effects of Overexposure:HEADEACHE,DIZZINESS,NAUSEA, LOSS OF  
COORDINATION.

Medical Cond Aggravated by Exposure:NONE GIVEN

=====  
===== First Aid Measures =====

First Aid:INHALATION;REMOVE FROM EXPOSURE,RESTORE BREATHING,KEEP WARM  
AND QUIET. SKIN;WASH AFFECTED AREA WITH SOAP AND  
WATER, REMOVE

CONTAMONATED CLOTHING AND LAUNDRER BEFORE REUSE. EYES; FLUSH WITH  
WATER FOR 1 5 MINUTES,GET MEDICAL ATTENTION. INGESTION; DO NOT GIVE  
ANYTHING BY MOUTH TO AN UNCOUNSCIOUS INDIVIDUAL, DO NOT INDUCE  
VOMITING, GIVE SEVERAL GLASSES OF WATER, KEEP WARM

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:102F,39C

Lower Limits:0.5

Upper Limits:7.5

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Proc

edures:WEAR FULL PROTECT CLOTHING AND SCBA, WATER MAY  
BE INEFFECTIVE,IF USED FOG NOZZLES ARE PREFERRABLE, WATER MAY BE  
USED TO COOL CONTAINERS EXPOSED EXTREME HEAT.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT,

=====  
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE, REMOVE ALL SOURCES OF IGNITION.  
REMOVE WITH AN INERT ABSORBENT.

Neutralizing Agent:NA

=====  
===== Handling and  
Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT ,SPARKS AND OPEN  
FLAMES. KEEP CONTAINER CLOSED, KEEP AWAY FROM CHILDREN

Other Precautions:USE APPROVED BONDING AND GROUNDING PROCEDURES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH/MSHA APPROVED RESPIRATOR IF TLVS ARE  
EXCEEDED

Ventilation:LOCAL

Protective Gloves:YES

Eye Protection:SAFETY WITH UNPERFORATED SIDE SHIELDS.

Other Protective Equipmen

t:NA  
Work Hygienic Practices:PRUDENT  
Supplemental Safety and Health  
NA

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:222F,106C  
Vapor Pres:UNK  
Vapor Density:> AIR  
Spec Gravity:0.85-1.20  
Evaporation Rate & Reference:< ETHER  
Solubility in Water:NA  
Appearance and Odor:ORANGE LIQUID  
Percent Volatiles by Volume:57-83

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE GIVEN  
Stabil  
ity Condition to Avoid:NONE GIVEN  
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,  
OXIDES OF METAL

===== Disposal Considerations =====

Waste Disposal Methods:MUST BE TESTED FOR IGNITABILITY. INCINERATE IN  
AN APPROVED FACILITY, DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE  
OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REQUIREMENTS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated f  
or use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.