

LAGOVEN SA -- DIESEL FUEL, ARTIC

=====
MSDS Safety Information
=====

FSC: 9140
NIIN: 00-286-5282
MSDS Date: 10/15/1991
MSDS Num: BMZSZ
Product ID: DIESEL FUEL, ARTIC
MFN: 01
Responsible Party
Cage: 0H7E2
Name: LAGOVEN SA
Address: ANARTADO 889
City: CARACAS 10010A NK 00000
Country: VN
Pr
Preparer's Name: RAOT
Published: Y

=====
Contractor Summary
=====

Cage: 0H7E2
Name: LAGOVEN SA
Address: ANARTADO 889
City: CARACAS 10010A NK 00000
Country: VN
Phone: UNKNOWN
Cage: 0CYF2
Name: REFINERY ASSOCIATES OF TEXAS INC
Address: 1150 HWY 46 S
City: NEW BRAUNFELS TX 78130
Phone: 512-620-4166

=====
Item Description Information
=====

=====
Item Name: DIESEL FUEL
Specification Number: VVF800GRADEDFAAR
Type/Grade/Class: GRADE DF-A
Unit of Issue: CN
Quantitative Expression: 00000000005GL
UI Container Qty: 0
Type of Container: CAN

=====
Ingredients
=====

Name: HYDROCARBONS (LIGHT MIXTURE)
% Wt: > 97 %
Other REC Limits: 5 MG/M3 AS OIL MIST
OSHA PEL: UNKNOWN
ACGIH TLV: UNKNOWN

Cas: 91-20-3
RTECS #: QJ0525000
Name: NAPHTHALENE (SARA III)
% Wt: < 3 %
Other REC Limits: NONE SPECIFIED
OSHA PEL: 10 PPM/15 STEL
ACGIH TLV: 10 PPM/15 STEL; 9192
EPA Rpt Qty: 100 LBS
DOT Rpt Qty: 100 LBS

Cas: 107-21-1
RTECS #: KW2975000
Name: ETHYLENE GLYCOL (SARA III) (MAY BE AN INGREDIENT)
% Wt: .10-.15
Other REC Limits: NONE SPECIFIED
OSHA PEL: C 50 PPM
ACGIH TLV: C 50 PPM,VAPOR; 9192
EPA Rpt Qty: 1 LB
DOT Rpt Qty: 1 LB
=====

=====
Health Hazards Data
=====

=====
Handling and Disposal
=====

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: PMCC
Flash Point Text: 100F,38C
Lower Limits: 0.7 %
Upper Limits: 5.0 %
Extinguishing
Media: DRY CHEMICAL, FOAM OR CARBON DIOXIDE OR WATR FOG.
Fire Fighting Procedures: DO NOT ENTER ANY ENCLOSED OR CONFINED FIRE SPACE
WITHOUT PROPER PROTECTIVE EQUIPMENT. COOL TANKS AND CONTAINERS EXPOSED TO
FIRE WITH WATER.
Unusual Fire/Explosion Hazard: TRANSFER PRODUCT BETWEEN COMMONLY GROUNDED
CONTAINERS. CONTAMINATED ITEMS IN CLOSED AREA MAY UNDERGO SPONTANEOUS
COMBUSTION.
=====

=====
Control Measures
=====

=====

=====

Physical/Chemical Properties

=====

HCC: F4

B.P. Text: 300-540F

M.P/F.P Text: NOT GIVEN

Decomp Text: UNKNOWN

Vapor Pres: NOT GIVEN

Vapor Density: NOT GIVEN

Spec Gravity: .77-.84

Evaporation Rate & Reference: NOT GIVEN

Solubility in Water: NEGLIGIBLE

Appearance and Odor: COLORLESS LIQUID WITH KEROSENE ODOR

Corrosion Rate: UNKNOWN

=====

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condition To Avoid: HEAT AND IGNITION SOURCES

Materials To Avoid: STRONG OXIDIZERS

=====

Toxicological Information

=====

Ecological Information

=====

=====

=====

MSDS Transport Information

=====

Regulatory Information

=====

Other Information

=====

HAZCOM Label

=====

=====

Product ID: DIESEL FUEL, ARTIC

Cage: 0H7E2

Company Name: LAGOVEN SA

Street: ANARTADO 889

City: CARACAS 10010A NK

Zipcode: 00000

Country: VN

Label Required IND: Y

Date Of Label Review: 06/24/1992

Status Code: C

MFG Label NO: NONE

Label Date: 06/24/1992

Origination Code: G

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Moderate

Reactivity Hazard: None

Hazard And Precautions: STORE IN A COOL, WELL-VENTILAT

TED AREA AWAY FROM HEAT

AND IGNITION SOURCES. CONTAINERS SHOULD ALWAYS BE KEPT CLOSED IN STORAGE AND

PROPERLY LABELLED. FIRST AID: EYES: IMMEDIATLEY FLUSH EYES WITH LARGE

AMOUNTS OF WATER FOR 15 MINUTES HOLDING LIDS APART. SEEK MEDICAL ATTENTION.

SKIN: WASH CONTAMINATED AREAS WITH SOAP AND WATER. SEEK MEDICAL ATTENTION IF

SYMPTOMS RESULT. INHALATION: REMOVE TO FRESH A IR. IF BREATHING HAS STOPPED,

RESUSCITATE. IF BREATHNG DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.

INGESTION; D

O NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any

person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.