

BAKER SEALANTS & COATINGS COMPANY -- FILLER,WOOD,PLASTIC -- 8010-00-262-9172

=====
Product Identification
=====

Product ID:FILLER,WOOD,PLASTIC

MSDS Date:10/17/1989

FSC:8010

NIIN:00-262-9172

MSDS Number: BNCBK

=== Responsible Party ===

Company Name:BAKER SEALANTS & COATINGS COMPANY

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:1-800-424-9300 24 HRS

E

mergency Phone Num:1-201-333-6986 8 AM- 4 PM

Preparer's Name:MARIO NAVARRO

CAGE:FO833

=== Contractor Identification ===

Company Name:BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

=====
Composition/Information on Ingredients
=====

In

gred Name:ISOPROPANOL
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 6-8%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:4000 PPM

Ingred Name:ACETONE
CAS:67-64-1
RTECS #:SL3150000
Fraction by Wt: 19-22%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 25-35%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYE-SEV IRRIT.IF NOT REMOVED
PROMPTLY,INJURE EYE TISS.SKIN-FREQ/PROL CONTACT MAY IRRIT/CAUSE
DERMATITIS.INHALE-IRRIT RESP TRACT.HEADACHE,DIZZINESS,ARE
ANESTHETIC,MAY HAVE OTHER CENTRAL NERVOUS SYS EFF ECTS.INGEST-LOW
ORDER OF TOXICITY.SMALLAMOUNTS LIQ ASPIRATED INTO RESP SYS MAY
CAUSE BRONCHIPNEUMONIA/PULMONARY EDEMA.

M
Medical Cond Aggravated by Exposure:AS PER METHYL ETHYL KETONE-MINOR
EMBRYOTOXIC/FETOTOXIC EFFECTS HAVE BEEN OBSERVED IN LABORATORY
RATES.

===== First Aid Measures =====

First Aid:EYES-IMMED FLUSH W/LRG AMOUNTS WATER,LEAST 15 MIN.GET MED
ATTN.SKIN-IMMED WASH W/LRG AMOUNTS WATER/SOAP IF AVAIL.GET MED
ATTN.INHALE-IMMED REMOVE FROM EXPOSURE.ADM ART RESP IF BREATH
STOPPED.KEEP AT R EST.GET MED ATTN. INGEST-DO NOT INDUCE
VOMITING.KEEP AT

REST.GET MED ATTN.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:4F (ACETONE

Lower Limits:2.6

Upper Limits:12.8

Extinguishing Media:ALCOHOL FOAM,CARBON DIOXIDE FOAM.

Fire Fighting Procedures:AVOID UNNECESSARY EXPOSURE TO HEAT.DO NOT ALLOW MATERIAL TO BECOME DRY.MATERIAL BURNS RAPIDLY WITH INTENSE HEAT.

Unusual Fire/Explosion Hazard:DO NOT ALLOW SOLUTION TO BECOME DRY.DRY FILM BURNS RAPIDLY WITH INTENSE HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER-DO NOT ALLOW TO DRY. DIKE AREA, SHOVEL INTO CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:GROUND ALL MIXING TANKS AND DRUMS. STORE IN COOL AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS.

Ventilation:MECHANICAL-EXPLOSION PROOF MOTORS AND SWITCHES.

Protective Gloves:RUBBER GLOVES

Eye Protection:GOGGLES

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175F(79.4C)

Melt/Freeze Pt:M.P/F.P Text: