

OCCIDENTAL CHEM CORP. DIV OF OCCIDENTAL PETROLEUM -- CHROMIC ACID-FLAKE --  
6810-00-264-3939

===== Product Identification =====

Product ID:CHROMIC ACID-FLAKE

MSDS Date:06/17/1988

FSC:6810

NIIN:00-264-3939

MSDS Number: BNCBL

=== Responsible Party ===

Company Name:OCCIDENTAL CHEM CORP. DIV OF OCCIDENTAL PETROLEUM

Address:360 RAINBOW BOULEVARD SOUTH, SUITE 400

Box:728

City:NIAGARA FALLS

State:NY

ZIP:

14302

Country:US

Info Phone Num:716-286-3081

Emergency Phone Num:716-278-7021

CAGE:KO973

=== Contractor Identification ===

Company Name:OCCIDENTAL CHEM CORP. DIV OF OCCIDENTAL PETROLEUM

Address:360 RAINBOW BOULEVARD SOUTH, SUITE 400

Box:728

City:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

Phone:716-286-3081

CAGE:KO973

Company Name:OCCIDENTAL CHEMICAL CORPORATION

Address:5005 LYNDON B JOHNSON FWY

Box:City:DALLAS

State:TX

ZIP:75244-6198

Country:US

Phone:800-752-5151/972-404-3800

CAGE:0AH54

Company



BE AT INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE  
Extinguishing Media:PRODUCT IS NOT COMBUSTIBLE. WATER FOG, DRY CHEMICAL OR CARBON DIOXIDE MAY BE USED IN AREAS WHERE PRODUCT IS STORED.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:UNDER FIRE CONDITIONS, DECOMPOSING MATERIAL MAY FORM A HOT VISCOUS FOAM. OXIDIZER. AVOID CONTACT WITH ORGANIC MATERIALS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAKS. REMOVE AS MUCH AS POSSIBLE (E.G. VACUUM TRUCK). THEN TREAT THE SPILL AREA WITH A REDUCING AGENT TO CONVERT THE HEXAVALENT CHROMIUM TO THE TRIVALENT FORM AND NEUTRALIZE WITH A WEAK BASE. SOAK UP AND PROPERLY STORE. DO NOT FLUSH TO SEWER.  
Neutralizing Agent:SODIUM BICARBONATE, SODA ASH OR LIME. REDUCE WITH SODIUM BISULFITE, OR OTHERS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE IN CLOSE PROXIMITY TO COMBUSTIBLE MATERIALS. STORE IN TIGHTLY CLOSED CONTAINERS AWAY FROM SOURCES OF HEAT AND MOISTURE.  
Other Precautions:REDUCE WITH SODIUM BISULFITE, SODIUM SULFITE, FERROUS SULFATE OR FERROUS CHLORIDE. NEUTRALIZE TO A PH 7.5 WITH SODA ASH, CAUSTIC SODA

R LIME TO FORM A PRECIPITATE. DO NOT REUSE CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED DUST CARTRIDGE AND DUST/MIST PRE-FILTER RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:INDUSTRIAL GRADE RUBBER OR PVC

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE

VAPORS OR MISTS. \* MSDS RECEIVED FROM FOCAL POINT F (AIR FORCE). AIR FORCE IDENTIFIED THE NSN.

===== Physical/Chemical Properties =====

HCC:D3

Melt/Freeze Pt:=197.2C, 387.F

Spec Gravity:SOLID

pH:0.2-2

Solubility in Water:63% @ 25C

Appearance and Odor:SOLID DARK RED FLAKES OR POWDER; NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH ORGANIC MATERIALS, OILS, GREASES, OR ANY EASILY

OXIDIZABLE MATERIAL. PRODUCT IS HYGROSCOPIC.

Stability Condition to Avoid:UNDER NORMAL USE CONDITIONS, THIS PRODUCT IS STABLE.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. IF IN SOLUTION, MUST BE REDUCED TO TRIVALENT CHROMIUM FIRST AND THEN NEUTRALIZED TO FORM PRECIPITANT.

Discla

imer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.