

CHEMRAY COATING CORP -- STAIN, OIL SEMI-TRANSPARENT WOOD, EXT DK RE --  
8010-00-926-9129

===== Product Identification =====

Product ID:STAIN, OIL SEMI-TRANSPARENT WOOD, EXT DK RE

MSDS Date:01/10/1989

FSC:8010

NIIN:00-926-9129

MSDS Number: BNCGR

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-

1111

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

===== Composition/Information on Ingredients =====

Ingred Name:RULE 66 MINERAL SPIRITS

Fraction by Wt: 70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 5.36 LBS/GAL OR 643 GRAMS/LITER.

RTECS #:9999999VO

Ot

her REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:(ACIGH) (OSHA) 100 PPM (590 MG/M3) FOR  
8 HOUR WORK DAY. HIGH VAPOR CONCENTRATIONS (OVER 1000 PPM) ARE  
IRRITATING TO THE EYE & RESPIRATORY TRACT. MAY CAUSE HEADACHES &  
DIZZINESS. PROLONG SKIN CONTACT IRRITATES.

=====  
===== First Aid Measures =====

First Aid:EYE C  
CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION  
SUBSIDES. IF IRRITATION PERSISTES CALL A PHYSICIAN. SKIN CONTACT:  
REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND  
WATER. INHALATION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR,  
CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:103F,39C  
Lower Limits:.9  
Upper Limits:7  
Extinguishing Media:CA  
CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL.  
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT IN  
CONFINED AREAS. FOR ENCLOSED AREAS, WATER SPRAY, AVOID BREATHING  
VAPOR OR FUMES.  
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER  
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. KEEP FROM  
HEAT/SPARK/OPEN FLAME. ADD ABSORBENT (SAND,  
EARTH, SAWDUST) TO  
SPILL. VENT AREA (OPEN WINDOW/DOOR). LRG SPILL: KEEP PRODUCT FROM  
ENTERING SEWER & WATERCOURSE BY DIKING. ADVISE AUTHORITIES IF  
PRODUCT HAS ENTERED.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:PROPER SHIPPING NAME--PAINT. HAZARDOUS  
CLASSIFICATION--COMBUSTIBLE LIQUID ID NO UN1263.  
Other Precautions:REPORTS HAVE ASSOCIATED REPEATED & PROLONGED  
OCCUPATION OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN

& NERVOUS

SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING CONTENT MAY B E HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINE AREA.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60 FPM. MECHANICAL (GENERAL): USE EXPLOSION PROOF EQUIP. SPECIAL: USE ONLY W/ADEQUATE VENT.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:SPLA

SH GOGGLES OR FACE SHIELD.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR OTHER CLOTHING TO AVOID REPEATED SKIN CONTACT.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE AND KEEP CONTAINER CLOSED WHEN NOT IN USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:308F,153C

Melt/Freeze Pt:M.P/F.P Text: