

LITTON SYS INC/ELECTRONIC DEVICES DIV -- LITTON PN L5283-54 THEMALOX
995/BD-995/BERLOX/ALSIMAG 754 -- 5960-01-098-1168

===== Product Identification =====

Product ID:LITTON PN L5283-54 THEMALOX 995/BD-995/BERLOX/ALSIMAG 754

MSDS Date:12/01/1988

FSC:5960

NIIN:01-098-1168

MSDS Number: BNKMH

=== Responsible Party ===

Company Name:LITTON SYS INC/ELECTRONIC DEVICES DIV

Address:960 INDUSTRIAL RD

City:SAN

CARLOS

State:CA

ZIP:94070-4116

Country:US

Info Phone Num:(415) 591-8411

Emergency Phone Num:(415) 591-8411

CAGE:MO696

=== Contractor Identification ===

Company Name:LITTON ELECTRON DEVICES .

Address:960 INDUSTRIAL RD

Box:City:SAN CARLOS

State:CA

ZIP:94070

Country:US

Phone:650-591-8411

CAGE:80080

Company Name:LITTON SYS INC/ELECTRONIC DEVICES DIV

Address:960 INDUSTRIAL RD

City:SAN CARLOS

State:CA

ZIP:94070-4116

Country:US

Phone:(415) 591-8411

CAGE:MO696

===== Composition/Information on

Ingredients =====

Ingred Name:BERYLLIUM OXIDE (SUSPECTED ANIMAL & HUMAN CARCINOGEN BY
NTP & IARC)
CAS:1304-56-9
RTECS #:DS4025000
OSHA PEL:2 UG/CUM
ACGIH TLV:2 UG/CUM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: DUST MAY CAUSE
BERYLLIOSIS, COUGH, CHEST PAINS, SHORTNESS OF BREATH, WEIGHT LOSS,
WEAKNESS & FATIGUE.
Explanation of Carcinogenicity:BERYLLIUM OXIDE IS A SUSPECTED ANIMAL &
HUMAN CARCINOGEN.
Effects of Overexposure:INHALATION: DUST MAY CAUSE BERYLLIOSIS, COUGH,
CHEST PAINS, SHORTNESS OF BREATH, WEIGHT LOSS, WEAKNESS & FATIGUE.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN
ALL CASES.

===== Handling and Storage =====

Handling and Storage
Precautions:DON'T CRUSH, GRIND OR SAND BLAST.
Other Precautions:IF USE OR HANDLING DIFFERS FROM NORMAL USAGE OF
SHIPPED PRODUCT. CONTACT SUPPLIER FOR ASSISTANCE IN ESTABLISHING
SAFE PROCEDURES.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:4620F
Spec Gravity:2.86
Appearance and Odor:WHITE SOLID W/NO ODOR.

===== Stabili

ty and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: TEMPERATURES >2200F

Hazardous Decomposition Products: VOLATILE BERYLLIUM HYDROXIDE

===== Disposal Considerations =====

Waste Disposal Methods: LANDFILL SOLID FORMS IN ACCORDANCE W/LOCAL,
STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.