

FLEXITALLIC GASKET CO -- FLEXICARB FILLED SPIRAL WOUND GASKET -- 5330-01-324-9542

=====
Product Identification
=====

Product ID:FLEXICARB FILLED SPIRAL WOUND GASKET

MSDS Date:02/23/1990

FSC:5330

NIIN:01-324-9542

MSDS Number: BNNKW

=== Responsible Party ===

Company Name:FLEXITALLIC GASKET CO

Address:6915 LAPORTE ROAD

City:DEER PARK

State:TX

ZIP:77536

Country:US

Info Phone Num:713-479-3491

Emergency

Phone Num:713-479-3491

CAGE:58156

=== Contractor Identification ===

Company Name:FLEXITALLIC GASKET CO INC.

Address:6915 LAPORTE RD

Box:760

City:DEER PARK

State:TX

ZIP:77536

Country:US

Phone:713-479-3491

CAGE:58156

Company Name:KENNETH INDUSTRIAL PRODUCTS INC

Address:174 STATE STREET

Box:4020

City:MERIDEN

State:CT

ZIP:06450

Country:US

Phone:203-238-2623

CAGE:53181

=====
Composition/Information on Ingredients
=====

Ingred Name:GRAPHITE, NATURAL

CAS:7782-42-5

RTECS #:MD9659600

OSHA PEL:15 MPPCF RDUST
ACGIH TLV:2 MG/M3 RDUST; 9293

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:RAW MATERIAL IS A POWDER AND PROLONGED
OR REPEATED BREATHING OF POWDER CAN RESULT IN PNEUMOCONIOSIS. AS A
FINISHED PRODUCT, NORMAL USAGE DOES NOT GENERATE SIGNIFICANT
RESP
IRABLE DUST.
Effects of Overexposure:NONE CURRENTLY KNOWN.
Medical Cond Aggravated by Exposure:NONE CURRENTLY KNOWN.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION. EYE:
IMMEDIATELY FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING
EYELID. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP & WATER.
INGESTION: D O NOT INDUCE VOMITING. NOTHING BY MOUTHIF UNCONSCIOUS.
GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Autoignition Temp:Autoignition Temp Text:NONE
Extinguishing Media:NOT APPLICABLE. MEDIA SUITABLE FOR SURROUNDING
FIRE.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT. WILL NOT SUPPORT COMBUSTION.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM OR SWEEP.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
ER.

===== Handling and Storage =====

Handling and Storage Precautions:AS A FINISHED PRODUCT (SPIRAL-WOUND
GASKET), THERE ARE NO SPECIAL STORAGE OR HANDLING PRECAUTIONS.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT APPLICABLE.
Ventilation:NOT APPLICABLE.
Protective Gloves:WORK GLOVES
Eye Protection:SAFETY GLASSES
Work Hygienic Practices:MINIMIZE BREATHING

DUST. CLEANSE SKIN

THOROUGHLY AFTER CONTACT, BEFORE BREAKS AND MEALS, AND AT THE END OF WORK PERIODS.

Supplemental Safety and Health

NONE

=====
Physical/Chemical Properties
=====

HCC:N1

Spec Gravity:1.0

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK FLEXIBLE SHEET AND TAPE/NO ODOR.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition

Products:CO, CO2.

=====
Disposal Considerations
=====

Waste Disposal Methods:APPROVED LANDFILL, DISPOSAL METHOD MUST CONFORM TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all li

ability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.