

EASTMAN KODAK COMPANY -- 159 9844, T-MAX DEVELOPER (CONCENTRATE) -- 6750-01-281-4599

=====
Product Identification
=====

Product ID:159 9844, T-MAX DEVELOPER (CONCENTRATE)

MSDS Date:11/15/1995

FSC:6750

NIIN:01-281-4599

MSDS Number: BNPXN

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS

: 800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====
Composition/Information on Ingredients
==

=====

Ingred Name:DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX
CAS:63149-47-3
Fraction by Wt: 45-50%
Other REC Limits:NONE SPECIFIED

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 40-45%
Other REC Limits:NONE SPECIFIED

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9495
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA)
CAS
:7631-90-5
RTECS #:VZ2000000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PENIETIC ACID, PENTA SODIUM SALT
CAS:140-01-2
Fraction by Wt: 212F,>100C
Decomp Temp:Decomp Text:>293F,>145C
Vapor Pres:18 MM
Vapor Density:0.6
Spec Gravity:1.23
pH:8.3
Solubility in Water:COMPLETE
Appearance and Odor:COLORLESS LIQUID. AMINE ODOR.
Percent Volatiles by Volume:40-45

===== Stability and Reacti

vity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG ACIDS.

Stability Condition to Avoid: HOWEVER, MATERIAL CAN DECOMPOSE ABOVE 145C (293F). AVOID TEMPERATURES ABOVE 45C (113F).

Hazardous Decomposition Products: COMBUSTION WILL PRODUCE CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN, OXIDES OF SULFUR.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal

Methods: DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. FLUSH TO SEWER W/LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should

seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.