View NSN Online: https://aerobasegroup.de/nsn/6850-00-935-1082

SCOTT SPECIALTY GASES -- TRICHLOROTRIFLUOROETHANE -- 6850-00-935-1082

Product ID:TRICHLOROTRIFLUOROETHANE MSDS Date:01/01/1987 FSC:6850 NIIN:00-935-1082 MSDS Number: BNRGL === Responsible Party === Company Name: SCOTT SPECIALTY GASES Address: ROUTE 611 NORTH Box:D-11 City:PLUMSTEADVILLE State:PA ZIP:18949 Country:US Info Phone Num:215-766-8861 **Emergency Phone Num:2** 15-766-8861, 908-754-7700 CAGE:51847 === Contractor Identification === Company Name: SCOTT SPECIALTY GASES Address:6141 EASTON RD (6141 ROUTE 611) Box:310 City:PLUMSTEADVILLE State:PA ZIP:18934 Country:US Phone:215-766-8861/ FAX: 215-766-0416 CAGE:51847

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III) CAS:76-13-1 RTECS #:KJ4000000 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED OSHA PEL:1000PPM /1250STEL ACGIH TLV:1000PPM/1250STEL9192 Ozone Depleting Chemical:1

LD50 LC50 Mixture:LD 50 ORAL RAT 43000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: AN ANESTHETIC; INHALATION CAN PRODUCE ASPHYXIATION. HIGH CONDENTRATIONS INTERFERE WITH PSYCHOMOTOR FUNCTIONS, EXPRESSED AS EXCITEMENT AND INCOORDINATION. AT HIGHER CONCENTRATIONS, CARDIAC ARRHYTHMIAS IS POSSIBLE Explanation of Carcinogenicity: FREON 113 IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA. Effects of Overexposure: SUPPLIER DID NOT ADDRESS THIS FIELD. SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure: SUPPLIER DID NOT ADDRESS THIS FIELD. First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR, RESTORE AND/OR SUPPORT BREATHING IF NECESSARY. EYE: FLUSH WITH W ATER FOR AT LEAST 15 MIN. SKIN: WASH IMMEDIATELY WATER. REMOVE CONTAMINATED CLOTHING. INGESTED: GET MEDICAL ATTENTION IMMEDIATELY. Flash Point:NON-FLAMMABLE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPIATE FOR SURROUNDING FIRE. Fire Fighting Procedures: USE SELF CONTAINED BREATHING APPARATUS FOR PROTECTION AGAINST VAPORS. Unusual Fire/Explosion Hazard:TO XIC AND CORROSIVE VAPORS MAY BE PRODUCED IN A FIRE SITUATUATION.

Spill Release Procedures: VENTILATE AND EVACUATE AREA. WEAR SELF CONTAINED RESPIRATOR.RESIDUES OR SMALL SPILLS MAY BE COLLECTED ON ABSORBENT MATERIAL. TRANSFER TO COVERED METAL DRUMS FOR RECOVERY OR DISPOSAL. CONFINE SPILLS AN D DO NOT ALLOW FUNOFF TO SEWER. Neutralizing Agent:NONE

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS IN A COOL, WELL- VENTILATED AREA. KEEP VAPORS AWAY FROM FLAMES, AREC WELDING, HIGH TEMPERATURE SURFACES, ETC.

Other Precautions: PROTCT CONTAINERS FROM PHYSICAL DAMAGE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:APPROVED RESPIRATOR EQUIPMENT SHOULD BE AVAILABLE FOR NON ROUTINE AND EMERGENCY USE. SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED IN EMERGENCIES. Ventilati on:PROVIDE ADEQUATE GENERAL AND LOCAL EXHAUST VENTILATION TO KEEP EXPOSURE BELOW TLV, ESPECIALLY SUMPS AND LOW AREAS. Protective Gloves:PROTECTIVE Eye Protection:GOGGLES Other Protective Equipment:WEAR PROTECTIVE GLOVES,GOGGLES AND CLOTHING WHEN LIQUID CONTACT IS POSSIBLE. PROVIDE EYE WASH STATION AND SAFETY SHOWER. Work Hygienic Practices:SUPPLIER DID NOT ADDRESS THIS FIELD. Supplemental Safety and Health MSDS RECEIVED FROM NAVY (FOCAL POINT N). NAVY IDENTIFIED NSN.

HCC:T6 Boiling Pt:B.P. Text:118F,48C Decomp Temp:Decomp Text:482F,250C Vapor Pres:285 MM Vapor Density:6 Spec Gravity:1.57 Evaporation Rate & amp; Reference:0.45 ACETONE = 1) Solubility in Water:0.028% Appearance and Odor:COLORLESS LIQUID, SWEET ETHER-LIKE ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES REACTS VIOLENTLY WITH ACTIVE METALS S UCH AS ALKALI OR ALKALINE EARTH METALS-POWDERED AL,ZN,BE,ETC. Stability Condition to Avoid:SUPPLIER DID NOT ADDRESS THIS FIELD. Hazardous Decomposition Products:DECOMPOSED BY HIGH TEMPERATURES FORMING HALOGENALIDS, HALOGENS, AND CARBONYL HALIDES. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:WHEN FEASABLE, WASTE SOLVENT SHOULD BE RECOVERED BY FILTRATION OR DISTILLATION. DISPOSAL THROUGH

A LICENSED WSTE

DISPOSAL COMPANY SHOULD ALSO BE CONSIDERED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.