

FISKE BROTHERS REFINING CO -- 630-AAA, LUBRIPLATE -- 9150-00-993-6617

=====
Product Identification
=====

Product ID:630-AAA, LUBRIPLATE

MSDS Date:05/01/1987

FSC:9150

NIIN:00-993-6617

MSDS Number: BNRGV

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

Prep

arer's Name:ROBERT J. SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENT

=====
Hazards Ide

ntification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PROD

UCT HAS LOW ORDER OF ACUTE ORAL TOXICITY, (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/CLEAR WATER FOR AT LEAST 15 MINS OR UNTIL IRRIT SUBSIDES. IF IRRIT PERSISTS, CALL MD.

SKIN:REMOVE ANY CONTAM CLTHG

& WASH W/SOAP & WARM WATER. IF INJECTED BY HIGH PRESS UNDER SKIN, REGARDL ESS OF APPEARANCE OR ITS SIZE, CNTCT MDIMMED. DELAY MAY CAUSE LOSS OF AFFECTED PART OF BODY. INHAL:VAP PRESS IS VERY LOW & INHAL AT ROOM TEMP NOT A PROBLEM. IF OVERCOME BY VAP FROM HOT (SUPP DATA)

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:400F,204C

Lower Limits:0.9%

Upper Limits:7%

Extinguishing Media:FOAM, DRY

CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . COOL EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER W/SUITABLE PETROLEUM S

OLV OR ADD ABSORBANT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRER BEFORE REUSE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .
Ventilation:LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS.
Protective Gloves:OIL RESISTANT GLOVES.
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:OIL RESISTANT APRON IF NEEDED.
Work Hygienic Practices:CLEANSE SKIN THOROUGHLY AFTER CONTACT.
Supplemental Safety and Health
FIRST AID PROC:PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE AND CALL MD.
INGEST:CALL MD IMMEDIATELY.
DO NOT INDUCE VOMITING.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>550F,>288C
Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID
Vapor Pres:5
Spec Gravity:0.94-0.95
Evaporation Rate & Reference: