

MINE SAFETY APPLIANCES CO -- 461768 CALIBRATION CHECK GAS, 60 PPM CARBON --
6550-01-203-6242

===== Product Identification =====

Product ID:461768 CALIBRATION CHECK GAS, 60 PPM CARBON

MSDS Date:02/01/1988

FSC:6550

NIIN:01-203-6242

MSDS Number: BNRJM

=== Responsible Party ===

Company Name:MINE SAFETY APPLIANCES CO

Address:3880 MEADOWBROOK ROAD

City:MURRYSVILLE

State:PA

ZIP:15668-1753

Country:US

Info

Phone Num:412-325-1313

Emergency Phone Num:412-325-1313

CAGE:55799

=== Contractor Identification ===

Company Name:MINE SAFETY APPLIANCES CO DBA MSA

Address:3880 MEADOWBROOK RD

Box:City:MURRYSVILLE

State:PA

ZIP:15668-1753

Country:US

Phone:724-733-9272

CAGE:55799

===== Composition/Information on Ingredients =====

Ingred Name:CARBON MONOXIDE

CAS:630-08-0

RTECS #:FG3500000

Fraction by Wt: 0.006%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:25 PPM; 9293

Ingred Nam

e:OXYGEN
CAS:7782-44-7
RTECS #:RS2060000
Fraction by Wt: 22%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NITROGEN
CAS:7727-37-9
RTECS #:QW9700000
Fraction by Wt: 78%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:ASPHYXIAN; 9192

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT APPLICABLE.
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CARBON MONOXIDE TCLO (HUMAN) IS
REPORTEDLY 650 PPM/45 MI
NUTES. LCLO(HUMAN) 5000 PPM/5 MINUTES.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:EXPOSURE TO 500-1000 PPM MAY CAUSE HEADACHE,
RAPID BREATHING, NAUSEA, WEAKNESS, DIZZINESS AND CONFUSION.
Medical Cond Aggravated by Exposure:CARBON MONOXIDE BURDEN MAY
AGGRAVATE ANGINA PECTORIS. PREGNANT WOMEN ARE REPORTADLY MORE
SENSITIVE THAN OTHERS. EFFECTS OF CO EXPOSURE ARE AGGRAVATED BY
HEAVY
LABOR, HEAT STRESS & HIGH ALTITUDE.

===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE. ADMINISTER OXYGEN. CONSULT PHYSICIAN
IMMEDIATELY.

===== Fire Fighting Measures =====

Extinguishing Media:THIS GAS MIXTURE IS NOT FLAMMABLE.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual

Fire/Explosion Hazard:GAS UNDER PRESSURE, 300 PSIG AT 70F. DO NOT EXCEED 120F.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. AVOID BREATHING GAS.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:PROTECT CYLINDERS FROM PHYSICAL DAMAGE. STORE BELOW 120F. KEEP CYLINDER VALVES CLOSED WHEN NOT IN USE AND WHEN EMPTY.

Other Precautions:DO NOT DEFACE CYLINDERS/LABELS. HANDLE CYLINDERS WITH PROPER CAUTION. AVOID BREATHING GAS. USE IN WELL-VENTILATED AREAS. FOLLOW THE CALIBRATION PROCEDURE DETAILED IN THE MSA INSTRUCTION MANUAL PROVIDED WITH THE INSTRUMENT UNDER CALIBRATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DUE TO THE LIMITED AMOUNT OF GAS IN THE CYLINDER, AND THE LOW RELEASE RATE EMPLOYED IN INSTRUMENT CALIBRATION, RESPIRATORY PROTECTION IS NOT INDICATED UNDER CONDITIONS OF INTENDED USE.

Ventilation:MECHANICAL VENTILATION IS SUITABLE.

Protective Gloves:WORK GLOVES FOR HANDLING CYLINDERS.

Eye Protection:APPROVED SAFETY GLASSES OR FACE SHIELD.

Other Protective Equipment:SAFETY SHOES AND HEARING PROTECTION.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. USE PROPER CARE WHEN HANDLING AND STORING CYLINDERS.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:G3

Vapor Density:1

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS, ODORLESS GAS

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT PUNCTURE OR INCINERATE CYLINDER. BEFORE

RE

DISCARDING CYLINDER, SLOWLY RELEASE CONTENTS TO A SAFE EXHAUST.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.